



Garage Canopy LED Light, Power Select 45/60/70W, 3-CCT, IP65, 8400lm

- Power-select wattage: 45W, 60W, or 70W in one fixture
- 3-CCT switchable color temperature: 3000K, 4000K, 5000K
- 8,400 lumen output at 120 lm/W efficacy
- IP65 rated for outdoor and wet-location canopy installations
- ADC12 aluminum housing with polycarbonate lens
- 0-10V dimming for adjustable output control

OVERVIEW

The 1-CP-70PS-3CCT is a power-select LED canopy light designed for garage and covered outdoor applications. It supports three wattage settings (45W, 60W, and 70W) and offers 3-CCT color temperature adjustment (3000K/4000K/5000K), providing flexibility for a range of installation requirements.

The fixture delivers 8,400 lumens at rated output with an efficacy of 120 lm/W. Operating voltage is rated 120-277VAC, and the unit carries an IP65 rating for dust and water ingress resistance. A 0-10V dimming interface allows output adjustment beyond the fixed power settings. CRI is rated at 90, and the housing is built from ADC12 aluminum with a polycarbonate lens. Ambient operating range is -40°C to 40°C.

This product carries a 5-year warranty. Certifications listed in product documentation include UL, ETL, and DLC Premium.

SPECIFICATIONS

OPTICAL

Luminous Flux	8,400 lm
Efficacy	120 lm/W
Color Temperature	3,000K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	90
Beam Angle	80°
LED Lifetime	50,000 h
Light Color	White
Lens Type	Polycarbonate

MECHANICAL

Finish	White
Material	ADC12

ORDERING

Warranty	5 y
----------	-----

ELECTRICAL

Operating Voltage	120-277 V
Wattage	45-70 W
Dimmer Type	0 - 10V

ENVIRONMENTAL

IP Rating	IP65
Ambient Operating Temperature	-40-40 °C -40-104 °F

CERTIFICATIONS & COMPLIANCE

UL

UL Listed

ETL

ETL Listed

DLC

DesignLights Consortium Premium

APPLICATIONS

- Gas station and fuel canopy lighting
- Parking garage ceilings
- Covered walkways and breezeways
- Loading dock canopies
- Drive-through canopy structures

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	8,400 lm	db	high
efficacy_lm_per_w	120 lm/W	db	high
cct_k	3,000K / 4,000K / 5,000K	db	high
cct_selectable	Yes	db	high
cri	90	db	high
beam_angle_deg	80°	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
lens_type	Polycarbonate	db	high
operating_voltage	120-277 V	db	high
wattage	45-70 W	db	high
dimmer_type	0 - 10V	db	high
finish	White	db	high
material	ADC12	db	high
ip_rating	IP65	db	high
ambient_temp_c	-40-40 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.