



- ### 60W LED Canopy Light, 5000K, 7,800 Lumens, IP65, ETL Listed
- Delivers 7,800 lumens at 60W for 130 lm/W efficacy
 - 5000K color temperature with CRI greater than 70
 - IP65 rated for dust and water ingress protection
 - 120° beam angle for wide area coverage
 - ADC12 housing with polycarbonate lens in white finish
 - Rated for -40°C to 40°C ambient operation with 45,000h LED lifetime

OVERVIEW

The 1-CP-SP60W-5K-WH is a 60W LED canopy light for outdoor commercial and industrial applications such as gas station canopies, covered walkways, loading docks and parking structures. Its slim white ADC12 housing with polycarbonate lens suits installations where a low -profile fixture is required.

The fixture operates at 60W across a 120-277VAC input and delivers 7,800 lumens at 5000K, yielding an efficacy of 130 lm/W. A 120° beam angle provides area coverage, and the IP65 rating offers protection against dust and water ingress. CRI is rated over 70, and the fixture is rated for ambient operation from -40°C to 40°C.

This canopy light carries ETL listing and is backed by a 5-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	7,800 lm
Efficacy	130 lm/W
Color Temperature	5,000 K
CRI	70
Beam Angle	120°
LED Lifetime	45,000 h
Light Color	White
Lens Type	PolyCarbonate

MECHANICAL

Product Dimensions	13 × 11 × 6 in
Finish	White
Material	ADC12
Weight	6 lb

ORDERING

Warranty	5 y
----------	-----

ELECTRICAL

Operating Voltage	120-277 V
Wattage	60 W

ENVIRONMENTAL

IP Rating	IP65
Ambient Operating Temperature	-40-40 °C -40-104 °F



APPLICATIONS

- Gas station canopies
- Covered walkways
- Loading docks
- Parking structures
- Outdoor commercial corridors

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	7,800 lm	db	high
efficacy_lm_per_w	130 lm/W	db	high
cct_k	5,000 K	db	high
cri	70	db	high
beam_angle_deg	120°	db	high
led_lifetime_h	45,000 h	db	high
color	White	db	high
lens_type	PolyCarbonate	db	high
operating_voltage	120–277 V	db	high
wattage	60 W	db	high
product_dimensions	13 × 11 × 6 in	db	high
finish	White	db	high
material	ADC12	db	high
weight	6 lb	db	high
ip_rating	IP65	db	high
ambient_temp_c	–40–40 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.