



75W LED Canopy Light, 5000K, 9750 lm, IP65, 0-10V Dimming, White

- Delivers 9,750 lm at 75W for an efficacy of 130 lm/W
- Lumileds LED chips with CRI 80 and 50,000 h rated lifetime
- IP65 rated ADC12 housing in slim white finish
- Accepts 120-277VAC input at 50/60Hz with 0-10V dimming
- Rated for -40°C to 40°C ambient operating temperature
- ETL certified with 1-year warranty

OVERVIEW

The 1-CP-SP75W-5K-WH is a 75W LED canopy light designed for covered parking structures, fuel station canopies, loading docks, and similar commercial or industrial overhead applications. Its slim white ADC12 housing provides a low-profile installation profile suitable for surface or canopy-mount configurations.

The fixture operates at 75W and delivers 9,750 lumens at 5000K, yielding an efficacy of approximately 130 lm/W. It accepts 120-277VAC input at 50/60Hz, supports 0-10V dimming, and carries an IP65 rating for resistance to dust and water ingress. The light source uses Lumileds LED chips with a CRI of 80 and operates across an ambient temperature range of -40°C to 40°C with a 120° beam angle.

This fixture is ETL certified and carries a 1-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	9,750 lm
Efficacy	130 lm/W
Color Temperature	5,000 K
CRI	80
Beam Angle	120°
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Finish	White
Material	ADC12

ORDERING

Warranty	1 y
----------	-----

ELECTRICAL

Operating Voltage	120-277 V
Wattage	75 W
Dimmer Type	0 - 10V

ENVIRONMENTAL

IP Rating	IP65
Ambient Operating Temperature	-40-40 °C -40-104 °F



ETL Listed

APPLICATIONS

- Covered parking structures
- Fuel station canopies
- Loading docks
- Warehouse overhangs
- Outdoor walkway canopies

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	9,750 lm	db	high
efficacy_lm_per_w	130 lm/W	db	high
cct_k	5,000 K	db	high
cri	80	db	high
beam_angle_deg	120°	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
operating_voltage	120–277 V	db	high
wattage	75 W	db	high
dimmer_type	0 - 10V	db	high
finish	White	db	high
material	ADC12	db	high
ip_rating	IP65	db	high
ambient_temp_c	-40–40 °C	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.