



LED Bollard Light 7W 700lm 6000K 14-Inch Gray Aluminum Acrylic IP44

- 7W LED source delivers 700 lumens of cool white 6000K light
- IP44 rated for outdoor exposure to splashing water and particles
- Aluminum and acrylic construction sized at 14 inches in height
- Operates across a wide 120-240VAC input range
- Rated for 50,000 hours of LED lifetime
- Backed by a 1-year manufacturer warranty

OVERVIEW

The B Series LED Bollard (Gray) is a hardwired outdoor bollard fixture designed for pathway, landscape, and perimeter lighting applications. Its acrylic top diffuses light evenly across the coverage area, making it well suited for walkways, courtyards, and commercial exterior installations.

The fixture operates on a 7W LED source producing 700 lumens of cool white light at 6000K. It runs on a 120-240VAC input and carries an IP44 rating, confirming protection against solid particle ingress and water splashing from any direction. Construction combines an aluminum body with an acrylic diffuser top, with a 14-inch overall height and a 3.5in x 5.9in acrylic section, and a rated LED lifetime of 50,000 hours.

The fixture is backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	700 lm
Color Temperature	6,000 K
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	3.5in x 5.9in x 14in
Finish	Gray
Material	Acrylic and Aluminum

ORDERING

Warranty	1 y
----------	-----

ELECTRICAL

Operating Voltage	120-240 V
Wattage	7 W

ENVIRONMENTAL

IP Rating	IP44
-----------	------

APPLICATIONS

Pathway and walkway lighting

Landscape perimeter lighting

Courtyard and plaza illumination

Commercial exterior entryways

Parking area edge lighting

slug	value	source	confidence
lumens	700 lm	pdf	high
cct_k	6,000 K	pdf	high
led_lifetime_h	50,000 h	db	high
operating_voltage	120–240 V	db	high
wattage	7 W	db	high
product_dimensions	3.5in x 5.9in x 14in	pdf	medium
finish	Gray	pdf	high
material	Acrylic and Aluminum	pdf	high
ip_rating	IP44	pdf	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY