



Outdoor LED Bollard, 9 W E27, 3000 K, IP65 Aluminum, 125x170x600 mm, Black

- 9 W draw on AC 100-120 V supply
- IP65 waterproof enclosure for exposed outdoor sites
- Aluminum and PC body in a black finish
- 3000 K output at CRI 80 with a 120-degree beam
- E27 lamp holder in a 125×170×600 mm square bollard
- Rated 50,000-hour LED life, -25 to +50 degrees C ambient

OVERVIEW

Square-profile outdoor bollard luminaire with a black aluminum and PC body, sized 125×170×600 mm with a 170×170 mm flange. The E27 lamp holder accepts a standard screw-base lamp, suiting pathways, entry drives and landscaped grounds where a low-level fixed light source is required.

Rated at 9 W on AC 100-120 V, the fixture delivers a 120-degree beam at 3000 K with CRI 80 and an efficacy of 80 lm/W using SMD2835 LED lamping. The IP65-rated, waterproof enclosure operates from -25 to +50 degrees C, with a rated LED life of 50,000 hours.

Covered by a 2-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	80 lm
Efficacy	80 lm/W
Color Temperature	3,000 K
CRI	80
Beam Angle	120°
LED Chip Type	SMD2835
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	170*170MM
Finish	Black
Material	Aluminum + PC

ORDERING

Warranty	2 y
----------	-----

ELECTRICAL

Operating Voltage	120 V
Wattage	9 W

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Waterproof
Ambient Operating Temperature	-25-50 °C -13-122 °F

APPLICATIONS

- Pedestrian pathways and walkways
- Commercial entry drives and forecourts
- Landscaped grounds and planting beds
- Hotel and campus perimeter lighting
- Parking area borders

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	80 lm	pdf	high
efficacy_lm_per_w	80 lm/W	pdf	high
cct_k	3,000 K	db	high
cri	80	pdf	high
beam_angle_deg	120°	both	high
led_chip_type	SMD2835	pdf	high
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	pdf	high
wattage	9 W	pdf	high
product_dimensions	170*170MM	pdf	high
finish	Black	db	high
material	Aluminum + PC	pdf	high
ip_rating	IP65	db	high
environmental_rating	Waterproof	db	high
ambient_temp_c	- 25-50 °C	pdf	high
warranty_years	2 y	db	high

Specifications subject to change without notice.