



L - Shaped LED Path Light, 5W 3CCT 12V DC/AC, IP65, Bronze Die - Cast Aluminum

- 5 W draw with 200 lm output for low-voltage path runs
- 3CCT field selector for 3000 K, 4000 K or 5000 K
- 150-degree beam angle for wide walkway coverage
- IP65-rated die-cast aluminum housing in epoxy powder bronze
- CRI 90 rendering with 30,000-hour rated LED life
- ETL and FCC listed, backed by a 3-year warranty

OVERVIEW

An L-shaped LED path light for low-voltage landscape and walkway lighting. The angled form factor suits ground-level installations along pathways, driveways and building perimeters, with a die-cast aluminum housing finished in epoxy powder paint bronze (ORB).

The fixture draws 5 watts on 12 V AC/DC input, accepting 12-24 V, and produces 200 lumens across a 150-degree beam angle. A three-position selector sets 3000 K, 4000 K or 5000 K in the field, with CRI 90 for exterior color rendering. The IP65-rated housing is rated for wet locations, and the LED is rated for 30,000 hours over a -20 to 50 degree C working range. Overall dimensions are 6 in diameter by 21.92 in high.

This product is ETL and FCC listed and carries a 3-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	200 lm
Efficacy	40 lm/W
Color Temperature	3,000K / 4,000K / 5,000K
CRI	90
Beam Angle	150°
LED Lifetime	30,000 h

MECHANICAL

Product Dimensions	Dia 6" * 21.92" H
Finish	Antique Bronze
Material	Die-cast aluminum

ORDERING

Warranty	3 y
----------	-----

ELECTRICAL

Operating Voltage	12 V
Wattage	5 W

ENVIRONMENTAL

IP Rating	IP65
Ambient Operating Temperature	-20-50 °C -4-122 °F

CERTIFICATIONS & COMPLIANCE

ETL

ETL Listed

FCC

FCC

APPLICATIONS

- Residential walkways and garden paths
- Driveway and parking court edges
- Commercial landscape beds
- Building perimeter grounds
- Courtyard and patio borders

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	200 lm	pdf	high
efficacy_lm_per_w	40 lm/W	pdf	medium
cct_k	3,000K / 4,000K / 5,000K	db	high
cri	90	pdf	high
beam_angle_deg	150°	both	high
led_lifetime_h	30,000 h	pdf	high
operating_voltage	12 V	db	high
wattage	5 W	pdf	high
product_dimensions	Dia 6" * 21.92" H	db	high
finish	Antique Bronze	db	high
material	Die-cast aluminum	pdf	high
ip_rating	IP65	both	high
ambient_temp_c	-20-50 °C	pdf	medium
warranty_years	3 y	db	high

Specifications subject to change without notice.