L-Shape Brass Path Light, G4 Lamp Base, IP65, 12V Low Voltage, Die-Cast Aluminum

OVERVIEW

The LT2404A is an L-shape low-voltage path light from the Brass Collection, designed for landscape and exterior pathway applications. The housing is constructed from die-cast aluminum with a frosted polycarbonate lens, and the fixture accepts a G4 lamp base (lamp sold separately). It is available in ORB Brown and Matte Black finishes.

The fixture operates on an input voltage range of 9–17V AC/DC and requires a low-voltage transformer (sold separately). Maximum lamp wattage is 40W. The frosted PC lens and IP65-rated enclosure make it suitable for exposed outdoor installations. Lead wire is a pre-stripped 48-inch SPT-1W, 18 gauge.

The fixture carries an IP65 environmental rating. Per the datasheet, warranty coverage is 5 years for surface finish and lifetime for structure. ETL certification is noted in product records. A range of brass accessory risers, stakes, and canopies are available separately for mounting flexibility.

SPECIFICATIONS

Power	Up to 40 W
IP rating	IP65
Input voltage	9–17 V AC/DC
Dimensions	5.6 x 1 x 21.9 in
Warranty	5 years (finish); lifetime (structure)

DIMENSIONS



ORDERING INFORMATION

CATEGORY	MODEL	FINISH	LAMP	ACCESSORIES
POLI-LIGHT	LT2404A	ORB Brown MB Matte Black	2R 3R 4R	LT4509 Brass surface mount flat canopy LT4509A Brass surface mount canopy LT4509LT Brass riser 7" LT4509L9 Brass riser 9" LT4509L12 Brass riser 12" LT4509L15 Brass riser 15" LT4509L24 Brass riser 24" LT4509T5SS Brass extendable riser, DIA 0.50", 15.75"-29.63" long LT4511 Brass stake 10" long LT4509T15 Brass extendable riser DIA0.75" 15.75" - 29" long Please consult for details on other optional accessories.

Specifications subject to change without notice.

CERTIFICATIONS & COMPLIANCE

IP65

IP65

Specifications subject to change without notice.