



Outdoor LED Bollard, 10/18/25W Selectable, 3CCT, IP65, Black Die-Cast Aluminum

- Die-cast aluminum housing with extruded aluminum pole, black finish
- Lumileds 2835 LEDs with CRI 95 for accurate color rendering
- Field-selectable wattage: 10W, 18W, or 25W
- Field-selectable CCT: 3000K, 4000K, or 5000K
- IP65 rated for water-resistant outdoor use
- ETL listed, Class I construction, 120-277V input

OVERVIEW

The 1-G-R25-3CCT-BK-ETL is an outdoor LED bollard designed for pathway, landscape, and perimeter lighting applications. The housing is constructed from die-cast aluminum with an extruded aluminum pole and an injection-molded PC diffuser, finished in black. Lumileds 2835 LEDs provide the light source with a CRI of 95.

The fixture includes a wattage selector switch with three settings—10W, 18W, and 25W—and a 3-CCT switch covering 3000K, 4000K, and 5000K, allowing field configuration without fixture replacement. Input voltage is rated 120–277V, and the LED source is rated for 50,000 hours. The IP65 rating confirms water-resistant protection suitable for exposed outdoor installations. The driver carries a 5-year warranty.

This bollard is ETL listed and Class I construction. Nominal dimensions are 250mm × 250mm × 1000mm H.

SPECIFICATIONS

OPTICAL

Color Temperature	3,000K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	95
LED Lifetime	50,000 h
Light Color	White
Lens Type	Polycarbonate

MECHANICAL

Product Dimensions	250mm x 250mm x 1000mm H
Finish	Black
Material	Die-casting Aluminium body

ORDERING

Warranty	5 y
----------	-----

ELECTRICAL

Operating Voltage	120-277 V
Wattage	10-30 W

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Water Resistant



ETL Listed

APPLICATIONS

- Pathway lighting
- Landscape lighting
- Perimeter lighting
- Parking lot walkways
- Commercial outdoor common areas

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
cct_k	3,000K / 4,000K / 5,000K	db	high
cct_selectable	Yes	db	high
cri	95	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
lens_type	Polycarbonate	db	high
operating_voltage	120–277 V	db	high
wattage	10–30 W	db	high
product_dimensions	250mm x 250mm x 1000mm H	pdf	high
finish	Black	db	high
material	Die-casting Aluminium body	db	high
ip_rating	IP65	db	high
environmental_rating	Water Resistant	db	high
warranty_years	5 y	pdf	high

Specifications subject to change without notice.