



200W LED Area Light, 26000 Lumens, 5000K, Type 3 Distribution, Slipfitter Mount

- 200W LED area light rated for 26,000 lumens output
- Efficacy of 130 lm/W at 5000K color temperature
- Type 3 distribution with a 90° beam angle
- Die-cast ADC12 aluminum housing rated IP65
- Operates on 120-277VAC input, DLC listed
- Rated for ambient temperatures from -40°C to 40°C

OVERVIEW

This 200W LED area light is designed for commercial and industrial outdoor applications such as parking lots, roadways, and large open spaces. It uses a slipfitter mount and produces a Type 3 distribution pattern suited for perimeter and area lighting layouts.

The fixture outputs 26,000 lumens at 5000K with a CRI of 70 and an efficacy of 130 lm/W. It operates on 120-277VAC input and carries a 90° beam angle. The die-cast ADC12 aluminum housing is rated IP65 and is built to operate in ambient temperatures from -40°C to 40°C. The unit measures approximately 27 × 14 × 5 in and weighs 15 lb.

This product carries DLC certification and a 1-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	26,000 lm
Efficacy	130 lm/W
Color Temperature	5,000 K
CRI	70
Beam Angle	90°
LED Lifetime	45,000 h

MECHANICAL

Product Dimensions	27 × 14 × 5 in
Material	ADC12
Mounting	Slipfitter
Weight	15 lb

ORDERING

Warranty	1 y
----------	-----

ELECTRICAL

Operating Voltage	120-277 V
Wattage	200 W

ENVIRONMENTAL

IP Rating	IP65
Ambient Operating Temperature	-40-40 °C -40-104 °F



DesignLights Consortium

APPLICATIONS

- Commercial parking lots
- Roadway and street lighting
- Industrial yards and loading docks
- Perimeter security lighting
- Large open outdoor areas

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	26,000 lm	db	high
efficacy_lm_per_w	130 lm/W	db	high
cct_k	5,000 K	pdf	high
cri	70	db	high
beam_angle_deg	90°	db	high
led_lifetime_h	45,000 h	db	high
operating_voltage	120–277 V	db	high
wattage	200 W	db	high
product_dimensions	27 × 14 × 5 in	db	high
material	ADC12	db	high
mount_type	Slipfitter	pdf	high
weight	15 lb	db	high
ip_rating	IP65	db	high
ambient_temp_c	–40–40 °C	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.