



Underground LED Light 3W 24V DC, Green, 30° Beam, IP67 Stainless Steel

- 3W draw at 24V DC input for low-voltage landscape circuits
- 300 lumens of green output through a 30° directional beam
- IP67 rated for direct burial and standing water exposure
- Stainless steel and aluminum housing for corrosion resistance
- Rated LED lifetime of 50,000 hours
- CE certified, backed by a 1-year warranty

OVERVIEW

The 1-UG4-3-G-24V is a 3W underground LED light designed for in-ground installation along walkways, driveways, and garden beds. Its compact form factor and 30° beam angle allow it to accentuate specific landscape features with controlled, directional illumination.

Constructed from stainless steel and aluminum, the fixture carries an IP67 rating, making it suitable for direct ground burial and exposure to rain, irrigation, and standing water. It operates on 24V DC and delivers 300 lumens of green-colored output at 3W draw, with a rated LED lifetime of 50,000 hours.

The fixture is CE certified and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	300 lm
Beam Angle	30°
LED Lifetime	50,000 h
Light Color	Green

MECHANICAL

Product Dimensions	100*80mm
Finish	Black + Silver
Material	Stainless steel + Aluminum

ORDERING

Warranty	1 y
----------	-----

ELECTRICAL

Operating Voltage	24 V
Wattage	3 W

ENVIRONMENTAL

IP Rating	IP67
Ambient Operating Temperature	-20-40 °C -4-104 °F

CERTIFICATIONS & COMPLIANCE

CE

CE

APPLICATIONS

- Garden bed accent lighting
- Walkway and pathway illumination
- Driveway edge marking
- Landscape feature lighting

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	300 lm	db	high
beam_angle_deg	30°	db	high
led_lifetime_h	50,000 h	db	high
color	Green	db	high
operating_voltage	24 V	db	high
wattage	3 W	db	high
product_dimensions	100*80mm	db	high
finish	Black + Silver	db	high
material	Stainless steel + Aluminum	db	high
ip_rating	IP67	db	high
ambient_temp_c	-20-40 °C	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY