



Inground Well Light, 4-Inch, 5W RGB+CCT Bluetooth, 350 lm, 12V AC/DC, IP67

- 5 W draw producing 350 lm at 3000K
- 60-degree beam for uplighting facades, columns and trees
- Die-cast aluminum housing with PMMA lens
- IP67 construction for dust and temporary immersion
- Bluetooth app control for RGB and tunable white output
- 12V AC/DC input for low-voltage landscape circuits

OVERVIEW

A 4-inch smart inground well light for landscape and architectural grade-level illumination. Bluetooth app control enables RGB and tunable white adjustment without a dedicated hub, suiting hardscape, pathway, tree and facade uplighting where the fixture is set flush with grade.

The luminaire draws 5 watts at 12V AC/DC and delivers 350 lumens through a 60-degree beam at 3000K. Construction is die-cast aluminum with a PMMA lens, rated IP67 for dust ingress and temporary immersion. Overall dimensions are 4 inches by 3.38 inches, with ORB and black finishes available.

A 3-year manufacturer warranty is included.

SPECIFICATIONS

OPTICAL

Luminous Flux	350 lm
Efficacy	70 lm/W
Color Temperature	3,000 K
Beam Angle	60°

MECHANICAL

Product Dimensions	4 in x 3.38 in
Finish	Oil-rubbed bronze or black
Material	Die-cast aluminum with PMMA lens
Mounting	Inground

ORDERING

Warranty	3 y
----------	-----

ELECTRICAL

Operating Voltage	12 V
Wattage	5 W
Dimmer Type	Non-dimmable

ENVIRONMENTAL

IP Rating	IP67
Environmental Rating	Wet location

APPLICATIONS

- Landscape and garden uplighting
- Hardscape and walkway grade-level lighting
- Building facade and column accenting
- Commercial courtyard and plaza lighting
- Tree and feature illumination

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	350 lm	pdf	high
efficacy_lm_per_w	70 lm/W	pdf	medium
cct_k	3,000 K	pdf	high
beam_angle_deg	60°	pdf	high
operating_voltage	12 V	pdf	high
wattage	5 W	pdf	high
dimmer_type	Non-dimmable	pdf	high
product_dimensions	4 in x 3.38 in	pdf	high
finish	Oil-rubbed bronze or black	pdf	medium
material	Die-cast aluminum with PMMA lens	pdf	high
mount_type	Inground	pdf	high
ip_rating	IP67	pdf	medium
environmental_rating	Wet location	pdf	high
warranty_years	3 y	pdf	high

Specifications subject to change without notice.