



L Series Linear Wall Sconce, 14 W, 1400 lm, IP65, five selectable CCTs, black iron and acrylic

- 14 W draw with 1400 lm output for linear wall grazing
- IP65 waterproof housing rated for outdoor and indoor use
- Iron body with acrylic diffuser in a black finish
- Five selectable color temperatures from 2700 K to 5000 K
- Internal SMD 2835 LED strip with CRI above 80
- MeanWell driver with UL certification, 120-240 V input

OVERVIEW

The L Series Linear Wall Sconce is a surface-mounted outdoor luminaire in a 23.26-inch linear format, built from an iron housing with an acrylic diffuser in a black finish. It suits building facades, gates, porches, corridors and garden walls, and installs on a separable bottom plate that is anchored to the wall before the body is secured with screws.

Output is 1400 lumens from a 14 W internal SMD 2835 LED strip, with CRI above 80 and five selectable color temperatures at 2700 K, 3000 K, 3500 K, 4000 K and 5000 K. The sealed body carries an IP65 waterproof rating for exterior or interior placement and operates on 120-240 V.

The fixture uses a MeanWell driver with UL certification and is supported by a three-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,400 lm
Efficacy	100 lm/W
Color Temperature	2,700K / 3,000K / 3,500K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	80
LED Chip Type	SMD 2835

MECHANICAL

Product Dimensions	45*6*5.5cm
Finish	Black
Material	Iron and acrylic
Mounting	Wall mount with separable bottom plate
Weight	2.42 lb

ELECTRICAL

Operating Voltage	265 V
Wattage	14 W

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Waterproof

ORDERING

Warranty

3 y

DIMENSIONS & DIAGRAMS

	NO.	Model	Watts	(cm)	Dim	IP Rate	Voltage	CCT Optional	
	1	HF-WL10W-40-C	10W	L40*W5*H4	>80	IP65	AC90-265V	3000K 4000K 6000K 6CCT RGBIC RGBIC+WW RGBIC+CW	
	2	HF-WL14W-60-C	14W	L60*W5*H4					
	3	HF-WL18W-80-C	18W	L80*W5*H4					
	4	HFWL22W-100-C	22W	L100*W5*H4					
	5	HFWL26W-120-C	26W	L120*W5*H4					
	6	HFWL34W-150-C	34W	L150*W5*H4					
	7	HFWL40W-180-C	40W	L180*W5*H4					
	8	HFWL45W-200-C	45W	L200*W5*H4					
	9	HFWL54W-240-C	54W	L240*W5*H4					

DIMENSION

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Building facade and entry walls
- Hotel corridors and porches
- Garden and patio walls
- Gate and driveway columns
- Villa balconies

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,400 lm	db	high
efficacy_lm_per_w	100 lm/W	pdf	medium
cct_k	2,700K / 3,000K / 3,500K / 4,000K / 5,000K	both	high
cct_selectable	Yes	db	high
cri	80	pdf	medium
led_chip_type	SMD 2835	db	high
operating_voltage	265 V	pdf	high
wattage	14 W	pdf	high
product_dimensions	45*6*5.5cm	pdf	high
finish	Black	db	high
material	Iron and acrylic	pdf	high
mount_type	Wall mount with separable bottom plate	pdf	high
weight	2.42 lb	pdf	high
ip_rating	IP65	both	high
environmental_rating	Waterproof	db	high
warranty_years	3 y	both	high

REVIEW COPY