



L Series Linear Wall Sconce, 26 W, 2600 lm, 5CCT Selectable, IP65, 4 ft Black

- 26 W draw with 2600 lm output for roughly 100 lm/W
- Field-selectable 2700 K, 3000 K, 3500 K, 4000 K and 5000 K
- IP65 waterproof iron and acrylic housing in a black finish
- Internal SMD2835 LED strips rated above 80 CRI
- Hardwired to line, neutral and ground on a separate backplate
- UL certified and covered by a 2-year warranty

OVERVIEW

The L Series Linear Wall Sconce is a 4 ft surface-mounted outdoor luminaire built on an iron housing with an acrylic diffuser in a black finish. It hardwires to line, neutral and ground through a separate backplate, suiting building walls, hotel corridors, gates, porches, gardens and patios.

Output is 2600 lm at 26 W, approximately 100 lm/W, from internal SMD2835 LED strips rated above 80 CRI. Color temperature is selectable across 2700 K, 3000 K, 3500 K, 4000 K and 5000 K, and the fixture operates on 110-220 V. The IP65 waterproof enclosure measures 47.24 × 1.96 × 1.57 inches.

UL certified and covered by a 2-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	2,600 lm
Efficacy	100 lm/W
Color Temperature	2,700K / 3,000K / 3,500K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	80
LED Chip Type	SMD2835

MECHANICAL

Product Dimensions	46*9*6cm
Length	1.2 m 3.9 ft
Finish	Black
Material	Iron+Acrylic
Mounting	Surface wall mount with separate backplate
Weight	3.09 lb

ELECTRICAL

Operating Voltage	265 V
Wattage	10 W
Input Connection Type	Hardwired (line, neutral, ground)

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Waterproof

ORDERING

Warranty

2 y

DIMENSIONS & DIAGRAMS

	NO.	Model	Watts	(cm)	CRI	IP Rate	Voltage	CCT Optional
	1	HF-WL10W-40-C	10W	L40*W8*H4	>80	IP65	AC90-265V	3 000K 4000K 6000K 6CCT R GBIC RGBIC+WW R GB IC+CW R GB IC+3CCT
	2	HF-WL14W-60-C	14W	L60*W8*H4				
	3	HF-WL18W-80-C	18W	L80*W8*H4				
	4	HF-WL22W-100-C	22W	L100*W8*H4				
	5	HF-WL26W-120-C	26W	L120*W8*H4				
	6	HF-WL34W-150-C	34W	L150*W8*H4				
	7	HF-WL40W-180-C	40W	L180*W8*H4				
	8	HF-WL45W-200-C	45W	L200*W8*H4				
	9	HF-WL54W-240-C	54W	L240*W8*H4				

DIMENSION

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Building facades and exterior walls
- Hotel corridors and entry gates
- Porches and front-door surrounds
- Garden, patio and balcony walls
- Villa and residential accent walls

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	2,600 lm	db	high
efficacy_lm_per_w	100 lm/W	pdf	medium
cct_k	2,700K / 3,000K / 3,500K / 4,000K / 5,000K	both	high
cct_selectable	Yes	db	high
cri	80	pdf	high
led_chip_type	SMD2835	pdf	high
operating_voltage	265 V	pdf	high
wattage	10 W	pdf	high
input_connection_type	Hardwired (line, neutral, ground)	pdf	high
product_dimensions	46*9*6cm	pdf	high
length	1.2 m	pdf	medium
finish	Black	db	high
material	Iron+Acrylic	db	high
mount_type	Surface wall mount with separate backplate	pdf	high
weight	3.09 lb	pdf	high
ip_rating	IP65	both	high
environmental_rating	Waterproof	db	high
warranty_years	2 y	pdf	high

REVIEW COPY