



L Series Linear Wall Sconce, 26 W, 2600 lm, RGBIC with three - CCT selectable white, IP65

- 26 W input producing 2600 lm at 100 lm/W efficacy
- SMD 2835 LED array rated for 50,000 hours of service
- RGBIC color plus three selectable white CCT settings
- IP65 -rated iron and acrylic housing in a black finish
- 1200 × 80 × 40 mm linear profile for wall or pole mounting
- UL listed and covered by a two-year warranty

OVERVIEW

The L Series linear wall sconce is a 1200 mm architectural luminaire built for exterior and covered-entry applications on residential and light commercial buildings. The IP65-rated iron and acrylic housing carries a black finish and mounts to a wall or pole using a removable back plate wired to line, neutral and ground.

The fixture draws 26 W and delivers 2600 lumens for an efficacy of 100 lm/W using SMD 2835 LEDs rated for 50,000 hours at CRI above 80. Color output combines RGBIC channels with three selectable white color temperatures, and the driver accepts 120-277 V input.

UL listed. Backed by a two-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	2,600 lm
Efficacy	100 lm/W
Color Temperature	3,000 K
Selectable CCT	Yes
CRI	80
LED Chip Type	2835
LED Lifetime	50,000 h
Light Color	RGB + CCT

MECHANICAL

Product Dimensions	46*9*6cm
Length	1.2 m 3.9 ft
Finish	BLACK
Material	Iron+Acrylic
Mounting	Wall/Pole Mount
Weight	3.09 lb

ELECTRICAL

Operating Voltage	265 V
Wattage	10 W

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Waterproof

ORDERING

Warranty

2 y

DIMENSIONS & DIAGRAMS

	NO.	Model	Watts	(cm)	Unit	IP Rate	Voltage	CCT Optional
	1	HF-WL10W-40-B	10W	L40*W8*H4	>80	IP65	AC90-265V	3000K 4000K 6000K 6CCT RGBIC RGBIC+WW RGBIC+CW RGBIC+3CCT
	2	HF-WL14W-60-B	14W	L60*W8*H4				
	3	HF-WL18W-80-B	18W	L80*W8*H4				
	4	HFWL22W-100-B	22W	L100*W8*H4				
	5	HFWL26W-120-B	26W	L120*W8*H4				
	6	HFWL34W-150-B	34W	L150*W8*H4				
	7	HFWL40W-180-B	40W	L180*W8*H4				
	8	HFWL45W-200-B	45W	L200*W8*H4				
	9	HFWL54W-240-B	54W	L240*W8*H4				

DIMENSION

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Building facades and exterior walls
- Hotel corridors and entry gates
- Garden, patio and balcony walls
- Covered porches and front doors
- Villa and residential interior accent walls

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	2,600 lm	db	high
efficacy_lm_per_w	100 lm/W	db	high
cct_k	3,000 K	pdf	high
cct_selectable	Yes	db	high
cri	80	pdf	medium
led_chip_type	2835	db	high
led_lifetime_h	50,000 h	db	high
color	RGB + CCT	db	high
operating_voltage	265 V	pdf	high
wattage	10 W	pdf	high
product_dimensions	46*9*6cm	pdf	high
length	1.2 m	pdf	high
finish	BLACK	db	high
material	Iron+Acrylic	db	high
mount_type	Wall/Pole Mount	db	high
weight	3.09 lb	pdf	high
ip_rating	IP65	both	high
environmental_rating	Waterproof	db	high

slug	value	source	confidence
warranty_years	2 y	both	high

Specifications subject to change without notice.

REVIEW COPY