



L Series Linear Wall Sconce, 40 W, 4000 lm, 5 - CCT Selectable, IP65 Black Finish

- 40 W draw producing 4000 lm from SMD2835 LED strips
- Five selectable color temperatures: 2700 K to 5000 K
- IP65 waterproof construction for exterior wall mounting
- Iron housing with acrylic diffuser in a black finish
- 70.86 × 1.96 × 1.57 in linear profile for facade runs
- UL certified with a 3-year warranty

OVERVIEW

The L Series Linear Wall Sconce is a surface-mounted outdoor luminaire in a 70.86 in linear form factor, built from iron with an acrylic diffuser and finished in black. It suits building facades, entries, corridors and covered outdoor living areas where a continuous line of illumination is required.

The fixture draws 40 W and delivers 4000 lm from internal SMD2835 LED strips, with five selectable color temperatures from 2700 K to 5000 K to match adjacent lighting. It operates on 110-220 V and carries an IP65 waterproof rating for exposed exterior locations. The sconce separates into a bottom plate and lamp body for line, neutral and ground wiring at the existing wall box.

UL certified and supported by a 3-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	4,000 lm
Efficacy	100 lm/W
Color Temperature	2,700K / 3,000K / 3,500K / 4,000K / 5,000K
Selectable CCT	Yes
LED Chip Type	SMD2835

MECHANICAL

Product Dimensions	70.86×1.96×1.57 inches
Finish	Black
Material	Iron+Acrylic
Mounting	Wall surface mount

ORDERING

Warranty	3 y
----------	-----

ELECTRICAL

Operating Voltage	240 V
Wattage	10 W

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Waterproof

DIMENSIONS & DIAGRAMS

- 1. Remove the small screws on both sides of the lamp, and separate the bottom plate and the lamp body.
- 2.Install and reset the bottom plate on the wall.
- 3.Connect the fire line.zero line and ground wire of the lamp body to the wire in the existing wall box. and must use the wiring cap or connect tape when the wire is connected.
- 4.Install the lamp body on the bottom plate and then install the lamp with screws.



Installation Steps



2

INSTALLATION

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Building facades and exterior walls
- Hotel entries and corridors
- Porches, patios and balconies
- Garden and villa perimeter lighting
- Gate and front door illumination

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	4,000 lm	db	high
efficacy_lm_per_w	100 lm/W	pdf	medium
cct_k	2,700K / 3,000K / 3,500K / 4,000K / 5,000K	both	high
cct_selectable	Yes	db	high
led_chip_type	SMD2835	pdf	high
operating_voltage	240 V	pdf	high
wattage	10 W	pdf	high
product_dimensions	70.86×1.96×1.57 inches	db	high
finish	Black	db	high
material	Iron+Acrylic	db	high
mount_type	Wall surface mount	pdf	high
ip_rating	IP65	both	high

slug	value	source	confidence
environmental_rating	Waterproof	db	high
warranty_years	3 y	pdf	high

Specifications subject to change without notice.

REVIEW COPY