

## 24W Up-Down LED Wall Sconce, 5CCT Selectable, Dusk-to-Dawn Photocell, IP65

### OVERVIEW

The 1-W-S12x2-5CCT-BK is a 24W up-and-down LED wall sconce with an integrated dusk-to-dawn photocell sensor. Housed in die-cast aluminum with tempered glass and a matte black powder-coat finish, it is suited for outdoor applications including building facades, corridors, patios, walkways, and covered entries.

The fixture delivers 2,000 lumens at 95 lm/W from dual 12W SMD3030 LED arrays, with a 60° beam angle and a selectable color temperature spanning 2700K, 3000K, 3500K, 4000K, and 5000K. It operates on 100–277V AC, carries a CRI greater than 80, a power factor above 0.95, and is rated IP65 for wet location installation. Rated working temperature ranges from -4°F to 104°F with a lamp life of 30,000 hours.

The fixture is ETL and cETL listed, meeting applicable U.S. and Canadian electrical standards. A 3-year manufacturer warranty is included. The photocell can be disabled by placing the included cover over the sensor, providing manual override capability when required.

### SPECIFICATIONS

<b>Power</b>	24 W	<b>Input voltage</b>	100-277 Vac
<b>Luminous flux</b>	2000 lm	<b>Dimensions</b>	3.54 x 3.54 x 11.8 in
<b>CCT</b>	2700/3000/3500/4000/5000 K	<b>Rated life</b>	30000 hrs
<b>CRI</b>	80	<b>Warranty</b>	3 years
<b>Beam angle</b>	60 °	<b>Operating Temp F</b>	-4 to 104 °F
<b>IP rating</b>	IP65		

### CERTIFICATIONS & COMPLIANCE



IP65