



Outdoor LED Wall Light, 22 W Up and Down, 5CCT Selectable, 1600 lm, IP65, Die Cast Aluminum

- 22 W total input power across two 11 W up and down emitters
- 1600 lm output at 70 lm/W efficacy with CRI 80
- Field-selectable 2700 K, 3000 K, 3500 K, 4000 K and 5000 K
- IP65 die cast aluminum housing rated for wet locations
- 100-277 V input with power factor above 0.95
- ETL listed, 30,000-hour lamp life, 3-year warranty

OVERVIEW

A 14-inch up-and-down outdoor wall fixture built on a die cast aluminum housing with a black finish, intended for building entries, walkways, patios and pillars. The mounting bracket suits standard 4-inch junction boxes for wall or pole installation.

Total input power is 22 W across two 11 W emitters, delivering 1600 lm at 70 lm/W from SMD 3030 chips with a 60-degree beam and CRI 80. Field-selectable color temperature covers 2700 K, 3000 K, 3500 K, 4000 K and 5000 K in one fixture. The driver accepts 100-277 V with a power factor above 0.95, and the IP65 waterproof housing operates from -20 to 40 degrees C with a rated 30,000-hour lamp life.

The fixture is ETL listed and carries a 3-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,600 lm
Efficacy	70 lm/W
Color Temperature	2,700K / 3,000K / 3,500K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	80
Beam Angle	60°
LED Chip Type	SMD 3030
LED Lifetime	30,000 h
Light Color	White

ELECTRICAL

Operating Voltage	100-277 V
Wattage	22 W
Power Factor	0.95

MECHANICAL

Product Dimensions	55*42*30CM
Finish	Black
Material	Die Cast Aluminum
Mounting	Wall/Pole Mount
Weight	35.27 lb

COMPLIANCE

UL File Number	5002722
----------------	---------

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Waterproof
Ambient Operating Temperature	-20-40 °C -4-104 °F

ORDERING

Warranty	3 y
----------	-----

DIMENSIONS & DIAGRAMS

	Power Factor	>0.95
	LED Chip	SMD3030
	Beam Angle	60°
	Color Temperature	5CCT Tunable

DIMENSION

CERTIFICATIONS & COMPLIANCE



ETL Listed



UL Listed
5002722

APPLICATIONS

- Building entries and doorways
- Garden and walkway lighting
- Patios and balconies
- Column and pillar accent lighting
- Commercial facade and corridor lighting

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,600 lm	both	high
efficacy_lm_per_w	70 lm/W	db	high
cct_k	2,700K / 3,000K / 3,500K / 4,000K / 5,000K	both	high
cct_selectable	Yes	db	high
cri	80	db	high
beam_angle_deg	60°	both	high
led_chip_type	SMD 3030	db	high
led_lifetime_h	30,000 h	pdf	high
color	White	db	high
operating_voltage	100-277 V	pdf	high
wattage	22 W	pdf	high
power_factor	0.95	db	high
product_dimensions	55*42*30CM	pdf	high
finish	Black	db	high
material	Die Cast Aluminum	db	high
mount_type	Wall/Pole Mount	db	high
weight	35.27 lb	pdf	high
ip_rating	IP65	both	high
environmental_rating	Waterproof	db	high

slug	value	source	confidence
ambient_temp_c	-20-40 °C	db	high
ul_file_number	5002722	db	high
warranty_years	3 y	db	high

Specifications subject to change without notice.

REVIEW COPY