



LED Wall Pack, 60-120 W Field Selectable, 125 lm/W, 3CCT, IP65, Bronze Die-Cast Housing

- Field-selectable wattage across the 60-120 W range at 125 lm/W
- 3000 K, 4000 K and 5000 K CCT selection with CRI of 70
- 120-277 VAC input with 0-10 V dimming and integrated photocell
- IP65 die-cast aluminum housing with borosilicate prismatic glass lens
- 100-degree beam angle and 50,000-hour rated LED life
- UL listed and DLC qualified, 5-year warranty

OVERVIEW

The LUMIPRO Flat Series is a slim LED wall pack for building perimeters, entryways, loading areas and parking structures. The die-cast aluminum housing carries a bronze finish and a borosilicate prismatic glass lens, and a detachable mounting plate allows attachment to standard junction boxes or surface mounting with conduit entry.

Wattage is field selectable across the 60-120 W range at an efficacy of 125 lm/W, with 3000 K, 4000 K and 5000 K CCT selection, CRI of 70 and a 100-degree beam distribution. The driver accepts 120-277 VAC, supports 0-10 V dimming, and an integrated photocell provides dusk-to-dawn switching. IP65 construction and a -35 C to +45 C operating range suit exterior mounting; rated life is 50,000 hours.

UL listed and DLC qualified, with a 5-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	3,750 lm
Efficacy	125 lm/W
Color Temperature	3,000K / 4,000K / 5,000K
CRI	70
Beam Angle	100°
LED Chip Type	2835
LED Lifetime	50,000 h

ELECTRICAL

Operating Voltage	120-277 V
Wattage	30 W
Dimmer Type	0-10V

MECHANICAL

Product Dimensions	340×240×114mm
Finish	Bronze
Material	Die - cast aluminum housing, borosilicate prismatic glass lens
Mounting	Detachable mounting plate, junction box or surface mount
Weight	7.47 lb

ORDERING

Warranty	5 y
----------	-----

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Non - Waterproof
Ambient Operating Temperature	-35–45 °C -31–113 °F
Operating Humidity	RH<90%

DIMENSIONS & DIAGRAMS

				(mm&inch)				
	WP06-30W	3.39kg	3.83kg	340×240×114mm 13.4"×9.45"×4.49"	435×292×170mm 17.1"×11.5"×6.7"	1	1261PCS	2828PCS
	WP06-40W	3.39kg	3.83kg					
	WP06-60W	3.39kg	3.83kg					
	WP06-80W	3.49kg	3.93kg					
	WP06-100W	4.12kg	4.56kg					
	WP06-120W	4.12kg	4.56kg					

DIMENSION

CERTIFICATIONS & COMPLIANCE

UL UL Listed	DLC DesignLights Consortium
------------------------------------	---

APPLICATIONS

- Building perimeter and entryway lighting
- Loading docks and service yards
- Parking structures and stairwells
- Warehouse exterior walls
- Multifamily walkways

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	3,750 lm	pdf	high
efficacy_lm_per_w	125 lm/W	db	high
cct_k	3,000K / 4,000K / 5,000K	both	high
cri	70	pdf	high
beam_angle_deg	100°	pdf	high
led_chip_type	2835	pdf	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	120–277 V	pdf	high
wattage	30 W	pdf	high

slug	value	source	confidence
dimmer_type	0-10V	pdf	high
product_dimensions	340×240×114mm	pdf	high
finish	Bronze	db	high
material	Die-cast aluminum housing, borosilicate prismatic glass lens	pdf	high
mount_type	Detachable mounting plate, junction box or surface mount	pdf	high
weight	7.47 lb	pdf	high
ip_rating	IP65	pdf	high
environmental_rating	Non - Waterproof	db	high
ambient_temp_c	-35-45 °C	pdf	high
operating_humidity	RH<90%	pdf	high
warranty_years	5 y	pdf	high

Specifications subject to change without notice.

REVIEW COPY