



LED Wallpack, 26W, 3,000 lm, 3000K, Frosted Acrylic Lens, Dusk-To-Dawn Photocell

- 26W draw with 3,000 lumen output at 115 lm/W efficacy
- 3000K color temperature with 70 CRI minimum
- Philips Lumileds SMD3030 LEDs rated for 50,000 hours
- 120-277VAC input, 50/60Hz, power factor above 0.9
- IP65 construction qualified from -40 °C to +50 °C ambient
- Precision-molded acrylic lens with integrated dusk-to-dawn photocell

OVERVIEW

The LUMIPRO Mini Series LED Wallpack is a compact wall-mounted luminaire for exterior commercial and industrial applications including building perimeters, entryways, pathways and parking areas. The frosted acrylic lens provides uniform distribution, and the integrated dusk-to-dawn photocell automates operation without additional controls. It replaces 75W MH or HID fixtures.

The fixture draws 26W and delivers 3,000 lumens at 3000K with 70 CRI and 115 lm/W efficacy, using Philips Lumileds SMD3030 LEDs rated for 50,000 hours. Input is 120-277VAC, 50/60Hz, and the luminaire is qualified for ambient temperatures from -40 °C to +50 °C with an IP65 rating for wet locations.

RoHS compliant. A five-year limited warranty is standard on the luminaire and components; this unit is offered as a Final Sale item carrying a limited 30-day warranty in place of the standard coverage.

SPECIFICATIONS

OPTICAL

Luminous Flux	3,000 lm
Efficacy	115 lm/W
Color Temperature	3,000 K
CRI	70
LED Chip Type	Philips Lumileds SMD3030
LED Lifetime	50,000 h
Lens Type	Acrylic

MECHANICAL

Product Dimensions	5.5 × 3.75 × 8.5 ft
Material	Acrylic lens
Mounting	Wall mount
Weight	1.8 lb

ELECTRICAL

Operating Voltage	120-277 V
Wattage	75 W
Current Draw *	0.21 A

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Suitable for wet locations
Ambient Operating Temperature	-40-50 °C -40-122 °F

ORDERING

Warranty

5 y

CERTIFICATIONS & COMPLIANCE

RoHS

RoHS Compliant

APPLICATIONS

- Building perimeter and facade lighting
- Commercial entryways and doorways
- Parking area and pathway illumination
- Loading docks and service corridors
- Industrial facility exterior walls

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	3,000 lm	db	high
efficacy_lm_per_w	115 lm/W	db	high
cct_k	3,000 K	pdf	high
cri	70	db	high
led_chip_type	Philips Lumileds SMD3030	pdf	high
led_lifetime_h	50,000 h	db	high
lens_type	Acrylic	db	high
operating_voltage	120–277 V	pdf	high
wattage	75 W	pdf	high
current_draw	0.21 A	pdf	low
product_dimensions	5.5 × 3.75 × 8.5 ft	db	high
material	Acrylic lens	pdf	high
mount_type	Wall mount	pdf	high
weight	1.8 lb	db	high
ip_rating	IP65	pdf	medium
environmental_rating	Suitable for wet locations	pdf	high
ambient_temp_c	–40–50 °C	db	high
warranty_years	5 y	db	high

* Value inferred from source data; verify before specification.
Specifications subject to change without notice.