



M Series LED Wallpack, 26W, 3000 lm, 3000K, 120-277 VAC, IP65 with Photocell

- 26W input producing 3,000 lumens at 115 lm/W efficacy
- 3000K color temperature with minimum 70 CRI output
- 120-277 VAC, 50/60 Hz input with power factor above 0.9
- Integral photocell provides dusk-to-dawn switching
- IP65 wet-location housing qualified from -40 °C to +50 °C
- RoHS compliant with 50,000-hour rated LED life

OVERVIEW

The Lumipro M Series 26W LED Wallpack is a building-mounted outdoor luminaire for doorway, pathway, perimeter and security illumination at commercial and industrial facilities. It serves as a replacement for 75W metal halide and HID wallpacks, with an integral photocell for dusk-to-dawn operation.

The fixture draws 26W on a 120-277 VAC, 50/60 Hz supply and delivers 3,000 lumens at 3000K with a minimum 70 CRI, an efficacy of 115 lm/W and a rated LED life of 50,000 hours. Precision-molded acrylic lensing shapes the distribution for wall-mounted applications, and the luminaire is qualified for ambient temperatures from -40 °C to +50 °C. The IP65 housing is suitable for wet locations and has been endurance tested to 3,000 hours of elevated ambient salt fog per ASTM B117.

The unit is RoHS compliant and carries a five-year limited warranty on luminaire and components.

SPECIFICATIONS

OPTICAL

Luminous Flux	3,000 lm
Efficacy	115 lm/W
Color Temperature	3,000 K
CRI	70
LED Chip Type	Philips Lumileds SMD3030
LED Lifetime	50,000 h
Lens Type	Acrylic

MECHANICAL

Product Dimensions	5.5 × 3.75 × 8.5 ft
Material	Acrylic lens with powder coat finish housing
Mounting	Wall mount
Weight	1.8 lb

ELECTRICAL

Operating Voltage	120-277 V
Wattage	75 W
Current Draw	0.21 A

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Suitable for wet locations
Ambient Operating Temperature	-40-50 °C -40-122 °F

ORDERING

Warranty

5 y

CERTIFICATIONS & COMPLIANCE

RoHS

RoHS Compliant

APPLICATIONS

- Building entrances and doorways
- Parking area and pathway lighting
- Loading docks and service yards
- Perimeter security lighting
- Multifamily breezeways and stairwells

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	3,000 lm	db	high
efficacy_lm_per_w	115 lm/W	db	high
cct_k	3,000 K	pdf	high
cri	70	db	high
led_chip_type	Philips Lumileds SMD3030	pdf	medium
led_lifetime_h	50,000 h	db	high
lens_type	Acrylic	db	high
operating_voltage	120–277 V	pdf	high
wattage	75 W	pdf	high
current_draw	0.21 A	pdf	medium
product_dimensions	5.5 × 3.75 × 8.5 ft	db	high
material	Acrylic lens with powder coat finish housing	pdf	medium
mount_type	Wall mount	pdf	high
weight	1.8 lb	db	high
ip_rating	IP65	pdf	high
environmental_rating	Suitable for wet locations	pdf	high
ambient_temp_c	–40–50 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.