



LED Wall Pack, 26W, 3,000 lm, 5000K,
Dusk-To-Dawn Photocell, Wet
Location Rated

- 26W input delivering 3,000 lumens at 115 lm/W efficacy
- 5000K color temperature with 70 CRI minimum output
- Precision-molded acrylic lens for building-mounted distribution
- Integral photocell provides dusk-to-dawn switching
- 120-277 VAC, 50/60 Hz input with power factor above 0.9
- RoHS compliant, wet location rated, 50,000 hour LED life

OVERVIEW

The Lumipro M Series LED Wall Pack is a building-mounted outdoor luminaire for perimeter security, walkways, doorways and service entrances. The compact housing suits facilities where a low-profile fixture replaces a 75W MH or HID wall pack.

The fixture operates at 26W and delivers 3,000 lumens at 5000K with 70 CRI, for an efficacy of 115 lm/W. Input is 120-277 VAC at 50/60 Hz with a power factor above 0.9. A precision-molded acrylic lens shapes the distribution, and the luminaire is qualified for ambient temperatures from -40 °C to +50 °C. Rated LED life is 50,000 hours. Dimensions are 5.5 × 3.75 × 8.5 and the unit weighs 1.8 lbs.

The luminaire is suitable for wet locations and is RoHS compliant. A five-year limited warranty applies to the luminaire and components.

SPECIFICATIONS

OPTICAL		ELECTRICAL	
Luminous Flux	3,000 lm	Operating Voltage	120-277 V
Efficacy	115 lm/W	Wattage	75 W
Color Temperature	5,000 K	Current Draw	0.21 A
CRI	70		
LED Chip Type	SMD3030		
LED Lifetime	50,000 h		
Lens Type	Acrylic		

MECHANICAL

Product Dimensions	5.5 × 3.75 × 8.5 ft
Finish	Super Durable thermoset powder coat, 3 mils minimum
Material	Acrylic lens with thermoset powder coat housing finish
Mounting	Wall mount
Weight	1.8 lb

ORDERING

Warranty	5 y
----------	-----

ENVIRONMENTAL

Environmental Rating	Suitable for wet locations
Ambient Operating Temperature	-40–50 °C -40–122 °F

CERTIFICATIONS & COMPLIANCE

RoHS

RoHS Compliant

APPLICATIONS

- Building perimeter security lighting
- Doorway and service entrance illumination
- Walkway and pathway lighting
- Loading dock and alley walls
- Warehouse and light industrial exteriors

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	3,000 lm	db	high
efficacy_lm_per_w	115 lm/W	db	high
cct_k	5,000 K	db	high
cri	70	db	high
led_chip_type	SMD3030	pdf	medium
led_lifetime_h	50,000 h	db	high
lens_type	Acrylic	db	high
operating_voltage	120–277 V	pdf	high
wattage	75 W	pdf	high
current_draw	0.21 A	pdf	medium
product_dimensions	5.5 × 3.75 × 8.5 ft	db	high
finish	Super Durable thermoset powder coat, 3 mils minimum	pdf	high
material	Acrylic lens with thermoset powder coat housing finish	pdf	high
mount_type	Wall mount	pdf	high
weight	1.8 lb	db	high
environmental_rating	Suitable for wet locations	pdf	high
ambient_temp_c	-40–50 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.