



Rounded LED Step Light, 2.5W, 170 lm, 3000K, 120-Degree Beam, Bronze, IP65

- 2.5 W draw with 170 lm output at 3000 K warm white
- 120-degree beam spread for broad tread and path washing
- Die-cast aluminum housing with glass lens in bronze finish
- IP65 construction rated for wet-location exterior use
- 50,000-hour rated LED service life
- ETL listed for North American installation

OVERVIEW

A rounded LED step light for stair risers, pathways and architectural accent lighting in residential and light commercial settings. The die-cast aluminum housing with glass lens and bronze finish suits recessed placement in walls, stringers and hardscape where a discreet, finished appearance is required.

The fixture draws 2.5 W at 24 V and delivers 170 lumens at 3000 K through a 120-degree beam, with a rated LED life of 50,000 hours. It is non-dimmable and carries an IP65 rating for wet-location installation.

ETL listed.

SPECIFICATIONS

OPTICAL

Luminous Flux	170 lm
Efficacy	68 lm/W
Color Temperature	3,000 K
Beam Angle	120°
LED Lifetime	50,000 h

MECHANICAL

Finish	Bronze
Material	Die-cast aluminum with glass lens

ELECTRICAL

Operating Voltage	24 V
Wattage	2.5 W
Dimmer Type	Non-dimmable

ENVIRONMENTAL

IP Rating	IP65
Environmental Rating	Wet location

CERTIFICATIONS & COMPLIANCE

ETL

ETL Listed

APPLICATIONS

- Exterior stair risers and step treads
- Walkway and pathway edge lighting
- Deck and patio perimeter walls
- Retaining wall and hardscape accent lighting
- Entry landings and porch steps

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	170 lm	pdf	high
efficacy_lm_per_w	68 lm/W	pdf	medium
cct_k	3,000 K	pdf	high
beam_angle_deg	120°	pdf	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	24 V	db	high
wattage	2.5 W	pdf	high
dimmer_type	Non - dimmable	pdf	high
finish	Bronze	pdf	high
material	Die - cast aluminum with glass lens	pdf	high
ip_rating	IP65	pdf	medium
environmental_rating	Wet location	pdf	high

Specifications subject to change without notice.