



## Corner Pole Tradeshow Extrusion, 2.8 x 2.8 cm Square Profile, 10 ft (3.05 m) Length

- Square 2.8 × 2.8 cm profile for space-restricted framing
- 10 ft (3.05 m) working length for booth and display builds
- Aluminum extrusion construction for indoor and outdoor service
- Supports 12 V lighting components with 135-degree beam spread
- Lighting components rated for 50,000 hours of service
- Covered by a 1-year warranty

### OVERVIEW

The Corner Pole is a square-profile structural pole used in fencing, signage installation, exhibition framing and general construction applications. Its compact 2.8 × 2.8 cm cross-section suits installations where space is limited, while its 10 ft (3.05 m) length accommodates a range of mounting and framing configurations in both residential and commercial settings.

Constructed for durability, the pole handles harsh weather conditions and heavy loads across outdoor and indoor environments. It carries a 13 × 3 mm profile detail and weighs 0.28 kg per meter, and it supports 12 V lighting components with a 135-degree beam spread rated for 50,000 hours of service.

Covered by a 1-year warranty.

### SPECIFICATIONS

#### OPTICAL

|              |          |
|--------------|----------|
| Beam Angle   | 135°     |
| LED Lifetime | 50,000 h |

#### ELECTRICAL

|                   |      |
|-------------------|------|
| Operating Voltage | 12 V |
|-------------------|------|

#### MECHANICAL

|                    |                   |
|--------------------|-------------------|
| Product Dimensions | 13*3mm            |
| Length             | 3.05 m<br>10.0 ft |
| Material           | Aluminum          |
| Weight             | 0.62 lb           |

#### ORDERING

|          |     |
|----------|-----|
| Warranty | 1 y |
|----------|-----|

APPLICATIONS

- Trade show booth framing
- Retail display structures
- Signage and lightbox installation
- Exhibition and event staging
- General construction framing

PROVENANCE — REVIEW COPY ONLY

| slug               | value    | source | confidence |
|--------------------|----------|--------|------------|
| beam_angle_deg     | 135°     | pdf    | high       |
| led_lifetime_h     | 50,000 h | db     | high       |
| operating_voltage  | 12 V     | pdf    | high       |
| product_dimensions | 13*3mm   | pdf    | high       |
| length             | 3.05 m   | pdf    | high       |
| material           | Aluminum | pdf    | medium     |
| weight             | 0.62 lb  | pdf    | high       |
| warranty_years     | 1 y      | db     | high       |

Specifications subject to change without notice.

REVIEW COPY