



Chrome-Finish 3-Way Corner Connector, Metal, 13 x 3 mm, for 4-PL3.2 LED Profile

- Metal body with chrome finish for corner transitions
- 3-way configuration for multi-directional profile junctions
- 13 × 3 mm section matched to the 4-PL3.2 profile series
- 12 V low-voltage system compatibility
- 135 degree beam spread maintained through the joint
- 50,000-hour rated LED lifetime with one-year warranty

OVERVIEW

The 4-PL3.2-CN is a 3-way corner connector designed for use with the 4-PL3.2 LED aluminum profile series. Constructed from metal with a chrome finish, it provides a clean, contemporary transition point at corners, supporting multi-directional profile runs in both commercial and residential architectural lighting installations.

The connector's 3-way configuration allows for flexible layout options, simplifying installation where profiles meet at a corner junction. It carries a 13 × 3 mm section, suits 12 V low-voltage profile systems, and maintains a 135° beam spread through the joined run. Unit weight is 0.28 kg.

Rated LED lifetime for the system is 50,000 hours, and the component is supplied with a one-year warranty.

SPECIFICATIONS

OPTICAL

Beam Angle	135°
LED Lifetime	50,000 h

ELECTRICAL

Operating Voltage	12 V
-------------------	------

MECHANICAL

Product Dimensions	13*3mm
Finish	Chrome
Material	Metal
Weight	0.62 lb

ORDERING

Warranty	1 y
----------	-----

APPLICATIONS

Tradeshow booth framing

Backlit fabric lightbox frames

Retail display signage

Interior architectural cove runs

Exhibition and display systems

slug	value	source	confidence
beam_angle_deg	135°	pdf	high
led_lifetime_h	50,000 h	db	high
operating_voltage	12 V	pdf	high
product_dimensions	13*3mm	pdf	high
finish	Chrome	pdf	high
material	Metal	pdf	high
weight	0.62 lb	pdf	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY