



Christmas Neon Sign, Santa 2 Motif,
100 x 85 cm Mirror Acrylic and PVC, 12
V DC, IP44

- Mirror acrylic and PVC backboard with FPC neon tubing
- 4 mm tube width for defined line detail on the Santa 2 motif
- IP44 rating for indoor and covered outdoor placement
- 12 V DC operation via 100-240 V AC adapter
- Rated -20 to 40 degrees C and 10-90 percent RH, non-condensing
- 100 × 85 cm panel at approximately 1 kg

OVERVIEW

A Santa 2 motif neon-style Christmas sign built on a mirror acrylic and PVC backboard with flexible FPC neon tubing at 4 mm width. The 100 × 85 cm format suits seasonal retail displays, hospitality interiors, event staging and brand or window graphics in both indoor and covered outdoor locations.

The sign operates on 12 V DC through a supplied adapter accepting 100-240 V AC input, and is rated IP44 for splash and particle protection. Rated operating range is -20 to 40 degrees C at 10 to 90 percent relative humidity, non-condensing. Luminous colors offered include red, yellow, blue, green, white and golden. Unit weight is approximately 1 kg.

Covered by a 2-year warranty for indoor installations and a 1-year warranty for outdoor installations from the date of delivery.

SPECIFICATIONS

ELECTRICAL

Operating Voltage	100-240 V
Input Connection Type	12 V DC adapter, 100-240 V AC input

ENVIRONMENTAL

IP Rating	IP44
Ambient Operating Temperature	-20-40 °C -4-104 °F
Operating Humidity	10-90% non-condensing

MECHANICAL

Product Dimensions	100*48CM
Strip Width	4 mm 0.16 in
Material	Mirror acrylic and PVC backboard, FPC neon tube
Weight	2.21 lb

ORDERING

Warranty *	2 y
------------	-----

APPLICATIONS

- Seasonal retail window displays
- Bar and cafe interior decor
- Holiday event and lobby staging
- Shopping center concourse displays
- Branded photo backdrops

slug	value	source	confidence
operating_voltage	100–240 V	pdf	high
input_connection_type	12 V DC adapter, 100 - 240 V AC input	pdf	high
product_dimensions	100*48CM	pdf	high
strip_width	4 mm	pdf	high
material	Mirror acrylic and PVC backboard, FPC neon tube	pdf	high
weight	2.21 lb	pdf	high
ip_rating	IP44	both	high
ambient_temp_c	-20–40 °C	pdf	high
operating_humidity	10 - 90% non - condensing	pdf	high
warranty_years	2 y	pdf	low

* Value inferred from source data; verify before specification.
Specifications subject to change without notice.

REVIEW COPY