



Double-End XH Power Feed Cable for CCT Flexible LED Sheet, 3 in.

- Double-ended XH connector configuration for two-point power feeding
- 3-inch overall cable length for compact, low-profile wiring runs
- Compatible with CCT flexible LED sheets rated for 50,000-hour LED lifetime
- Backed by a 1-year warranty
- Secure, stable connection maintains consistent power delivery

OVERVIEW

The 7-FS-XH-CA3D-3 is a 3-inch double-ended XH power feed cable designed for use with CCT flexible LED sheets. It serves as a direct power delivery interface between the driver or power source and the LED sheet, supporting clean, low-profile installations in both commercial and residential applications.

The cable is constructed for durable, long-term use and provides a secure, stable connection to maintain consistent power delivery to the LED sheet. Its double-ended configuration simplifies installation and supports a professional finished appearance, and it is intended for use with LED sheets rated for a 50,000-hour operating life.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

ELECTRICAL

Wire Length 3 in

ORDERING

Warranty 1 y

APPLICATIONS

- Backlit stone panels
- Illuminated countertops
- Feature wall lighting
- Retail display backlighting
- Architectural signage

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
wire_length	3 in	pdf	high
warranty_years	1 y	db	high

Specifications subject to change without notice.