



A19 Globe LED Bulb, 10W 4000K Day White, E27 Base, 850lm

- Delivers 850 lumens at 10W for efficient general lighting
- 4000K Day White color temperature with CRI of 80 or greater
- 270° beam angle provides wide, even light distribution
- Operates across a 120-240V input range for broad compatibility
- Rated for 50,000 hours of LED lifetime
- Plastic and aluminum construction weighing 0.2 lb

OVERVIEW

The 8-E27-A19-G10DW is a 10W A19 globe LED bulb designed for general-purpose illumination in both commercial and residential applications. Its E27 base provides broad fixture compatibility, and the compact 65×118mm form factor suits standard enclosed and open luminaires alike.

The bulb operates across a 120-240V range and delivers 850 lumens at a 4000K (Day White) color temperature, with a CRI of 80 or greater for reliable color accuracy and a 270° beam angle for broad-area coverage. Rated for 50,000 hours of LED lifetime, the plastic and aluminum construction keeps weight at 0.2 lb while supporting efficient heat management.

The bulb carries a 1-year manufacturer warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	850 lm
Color Temperature	4,000 K
CRI	80
Beam Angle	270°
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	65×118mm
Finish	White
Material	Plastic + Aluminum
Weight	0.2 lb

ELECTRICAL

Operating Voltage	120-240 V
Wattage	10 W

ORDERING

Warranty	1 y
----------	-----

APPLICATIONS

- Residential ceiling and table lamp fixtures
- Commercial open luminaires and pendant fixtures
- Enclosed fixtures requiring E27 base compatibility
- General-purpose ambient lighting in offices and retail spaces

slug	value	source	confidence
lumens	850 lm	db	high
cct_k	4,000 K	pdf	high
cri	80	db	high
beam_angle_deg	270°	db	high
led_lifetime_h	50,000 h	db	high
operating_voltage	120–240 V	db	high
wattage	10 W	db	high
product_dimensions	65×118mm	db	high
finish	White	db	high
material	Plastic + Aluminum	db	high
weight	0.2 lb	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY