

## LED Linear High Bay Light, 2 FT, 80/110/165W Selectable, 3-CCT, 120-277V

### OVERVIEW

The HB-L Series 9-HB-L165PS-3CCT is a 2-foot LED linear high bay fixture designed for indoor commercial and industrial applications including warehouses, supermarkets, gymnasiums, and production assembly areas. It is a direct replacement for HID high bay luminaires, utilizing SMD2835 solid-state technology for reduced maintenance and extended service life.

The fixture offers field-selectable wattage (80W, 110W, or 165W) and CCT selection across 3500K, 4000K, and 5000K, with a rated efficacy of 140 lm/W. Input voltage is 120–277VAC, accommodating a wide range of commercial electrical systems. The unit carries an IP20 rating, a CRI of 80 or greater, and a rated lifespan exceeding 50,000 hours. Standard 0–10V dimming is supported. Mounting hardware includes a ceiling hook and two chains.

The fixture is UL/cUL Listed and DLC 5.1 qualified, supporting eligibility for utility rebate programs. A 5-year manufacturer warranty is included.

### SPECIFICATIONS

<b>Power</b>	165 W	<b>IP rating</b>	IP20
<b>Luminous flux</b>	22275 lm	<b>Input voltage</b>	120-277 VAC
<b>CCT</b>	3500-6500 K	<b>Rated life</b>	50000 h
<b>CRI</b>	80	<b>Warranty</b>	5 years
<b>Beam angle</b>	85 °	<b>Operating temp</b>	-30 to +40 °C

### CERTIFICATIONS & COMPLIANCE



UL Listed



DesignLight

s  
Consortium