

Architectural Linear Suspension Square Installation Kit – Black

OVERVIEW

The 9-LG-Z-SIK-BK is a square suspension installation kit in black finish, designed for use with the SL8860 Architectural Linear Grid Series. It provides the mounting hardware required for suspended deployment of compatible SL8860 linear luminaires in commercial environments such as offices, hospitality spaces, and libraries.

This kit supports the square-style flexible mounting clip configuration used in suspended installations of the SL8860 series. The black finish coordinates with black-finish luminaire configurations available in the series. Compatibility spans 2 ft, 4 ft, and 8 ft luminaire lengths.

No independent certifications or warranty terms are confirmed for this accessory kit in available source data. Refer to the SL8860 series documentation for system-level specifications and installation requirements.

SPECIFICATIONS

Power	15/20/25 (2 ft), 30/40/50 (4 ft), 60/80/100 (8 ft) W	Input voltage	AC 120–277 V or AC 120–347 V (model dependent)
Luminous flux	1650/2200/2750 (2 ft, 120° optical)	Dimensions	2 ft: 23.3 depth x 4 in (592 x 98 x 60 mm); 4 ft: 23.3 depth x 8 in (592 x 196 x 60 mm); 8 ft: 23.3 depth x 16 in (592 x 392 x 60 mm) in (mm)
CCT	3000/4000/5000 (selectable via dip switch)	Weight	2 ft: 3.70 lb (1.68 kg); 4 ft: 6.61 lb (3.00 kg); 8 ft: 12.35 lb (5.60 kg)
CRI	3300/4400/5000 (CRI options)	Warranty	2 (2 years)
Beam angle	120 (standard lampshade); 80 (C1, C2, C3, C4, C5, C6, C7, C8, C9, C10, C11, C12, C13, C14, C15, C16, C17, C18, C19, C20, C21, C22, C23, C24, C25, C26, C27, C28, C29, C30, C31, C32, C33, C34, C35, C36, C37, C38, C39, C40, C41, C42, C43, C44, C45, C46, C47, C48, C49, C50, C51, C52, C53, C54, C55, C56, C57, C58, C59, C60, C61, C62, C63, C64, C65, C66, C67, C68, C69, C70, C71, C72, C73, C74, C75, C76, C77, C78, C79, C80, C81, C82, C83, C84, C85, C86, C87, C88, C89, C90, C91, C92, C93, C94, C95, C96, C97, C98, C99, C100) (16 ft options); 150, 50 (50°)		

DIMENSION

