

## Recessed Mounting Kit for 9-LP Architectural Linear Light Fixtures

### OVERVIEW

The 9-LP-Z-Clip-R is a recessed mounting kit designed for use with the 9-LP architectural linear light fixture series. It enables quick installation of the fixture into open ceiling applications, supporting recessed mounting as one of several available installation methods alongside pendant, surface, and wall configurations.

The compatible fixture line operates on 120–347V AC input and carries a 5-year warranty. Listings and compliance for the associated fixture include UL/CUL and DLC 5.1 certification.

Note: Specifications listed above reflect the compatible LI-J series fixture. Dimensional and weight data specific to this mounting kit are not available in current source documentation.

### SPECIFICATIONS

<b>Power</b>	15–25 (2 ft) / 30–50 (4 ft) / 60–100 (8 ft) W	<b>Input voltage</b>	120–347 VAC, 50/60 Hz V
<b>Luminous flux</b>	Up to 1620 lm/ft lm/ft	<b>Dimensions</b>	2 ft: 23-13/16" L x 2-61/64" W x 2-23/64" H
<b>CCT</b>	3000 / 3500 / 4000 / 5000 (selectable) K	<b>Weight</b>	2 ft: 1.5 kg; 4 ft: 2.5 kg; 8 ft: 4.7 kg
<b>CRI</b>	>80 standard; >90 optional (RA >50)	<b>Rated life</b>	50,000 hrs @ L70
<b>Beam angle</b>	120 °	<b>Warranty</b>	5 yr
<b>IP rating</b>	IP20	<b>Operating temp</b>	-25 to +40 °C

### WIRING

- DLC Premium, up to 1620LM/FT
- Direct and indirect lighting settings 70% direct / 30% indirect

#### Corners:

- Corners and other transition pieces are fully luminous
- Uses Male/Female connector to quickly connect power from the host fixture. (T.Y.V.120°) corners are also available

#### Finish:

- All painted surfaces are premium powder coated baked on for maximum durability and color stability
- W: White (RAI 9016); Black (RAI 9011); Silver (RAI 9006)

## CERTIFICATIONS & COMPLIANCE

---



UL Listed



DesignLight  
S  
Consortium