



Architectural Linear Fixture, 4 ft, 30-50 W Selectable, 4-CCT 3000-5000 K, IP20, White

- Field-selectable 30 W, 40 W or 50 W output at 115 lm/W efficacy
- Four-position CCT selection: 3000 K, 3500 K, 4000 K and 5000 K at 80 CRI
- 0-10 V dimming from a 120-347 VAC Class 2 driver, power factor above 0.9
- Extruded 6063 aluminum housing with white powder-coat finish
- SMD2835 LEDs rated 50,000 hours L80B20 with 120-degree beam angle
- UL and FCC listed, DLC 5.1 qualified, 5-year warranty

OVERVIEW

A 4 ft direct/indirect architectural linear luminaire with an extruded 6063 aluminum housing, die-cast end caps and a white powder-coat finish. Measuring 1205 × 60 × 75 mm, it suspends from a pendant kit or installs surface, wall or recessed, and screwless end caps with internal Quick-Link connectors allow continuous runs.

Wattage is field-selectable at 30 W, 40 W or 50 W and CCT is field-adjustable at 3000 K, 3500 K, 4000 K or 5000 K, with 80 CRI, a 120-degree beam and 115 lm/W efficacy. SMD2835 LEDs are rated 50,000 hours, the 120-347 VAC Class 2 driver holds a power factor above 0.9 with THD under 20 percent, and 0-10 V dimming is standard. The IP20 housing operates from -20 to 40 degrees C at 10 to 90 percent RH.

UL and FCC listed, DLC 5.1 qualified, and covered by a 5-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,620 lm
Efficacy	115 lm/W
Color Temperature	3,000K / 3,500K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	80
Beam Angle	120°
LED Chip Type	SMD2835
LED Lifetime	50,000 h

ELECTRICAL

Operating Voltage	120-347 V
Wattage	0.5 W
Power Factor	0.95
Dimmer Type	0 - 10V
Wire Length	59 in

MECHANICAL

Product Dimensions	1205×60×75mm
Finish	White
Material	Aluminum
Mounting	Wall/Pole Mount
Weight	3.31 lb

ORDERING

Warranty	5 y
----------	-----

ENVIRONMENTAL

IP Rating	IP20
Environmental Rating	Non - Waterproof
Ambient Operating Temperature	-20-40 °C -4-104 °F
Operating Humidity	10%-90% RH

DIMENSIONS & DIAGRAMS

- DLC Premium, up to 1620LM/FT
- Direct and indirect lighting settings 70% direct / 30% indirect

Corners:

- Corners and other transition pieces are fully luminous
- Uses Male/Female connector to quickly connect power from the last fixture. L, T, X, Y (120°) corners are also available.

Finish:

- All painted surfaces are premium powder coated baked on for maximum durability and color stability
- W: White RAL 9016; Black (RAL 9011); Silver (RAL 9006)

WIRING

CERTIFICATIONS & COMPLIANCE

UL

UL Listed

DLC

DesignLights Consortium

FCC

FCC

APPLICATIONS

Open-plan office ceilings

School and university corridors

Healthcare circulation areas

Retail sales floors

Conference and training rooms

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,620 lm	pdf	high
efficacy_lm_per_w	115 lm/W	db	high
cct_k	3,000K / 3,500K / 4,000K / 5,000K	both	high
cct_selectable	Yes	db	high
cri	80	db	high
beam_angle_deg	120°	both	high
led_chip_type	SMD2835	db	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	120-347 V	pdf	high
wattage	0.5 W	pdf	high
power_factor	0.95	db	high
dimmer_type	0 - 10V	db	high
wire_length	59 in	pdf	medium
product_dimensions	1205×60×75mm	db	high
finish	White	db	high
material	Aluminum	db	high
mount_type	Wall/Pole Mount	db	high
weight	3.31 lb	pdf	high
ip_rating	IP20	both	high
environmental_rating	Non - Waterproof	db	high
ambient_temp_c	-20-40 °C	db	high

slug	value	source	confidence
operating_humidity	10% - 90% RH	pdf	high
warranty_years	5 y	both	high

Specifications subject to change without notice.

REVIEW COPY