



1x2 LED Grilled Panel Light, 20W,
6000K Cool White, 120-277V AC

- 20W power consumption for energy-efficient interior lighting
- 6000K cool white color temperature for clear task visibility
- 120-277V AC input voltage supports wide electrical compatibility
- 50,000-hour rated LED lifetime for extended service life
- 1-year manufacturer warranty included
- 1x2 ft panel format fits standard drop-ceiling grids

OVERVIEW

The 9-P1x2-20W-H is a 1x2 ft LED grilled panel light designed for general indoor illumination in commercial and light industrial environments. Its low-profile, uniform-diffusion design suits drop-ceiling grid installations in offices, corridors, and similar interior spaces.

The fixture operates at 20W with a 6000K cool white color temperature, suitable for task-oriented environments requiring clear visibility. Operating voltage is rated for 120-277V AC, providing compatibility across a wide range of electrical systems without additional hardware. The LED source carries a rated lifetime of 50,000 hours.

The fixture is backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

Color Temperature	6,000 K
LED Lifetime	50,000 h

ELECTRICAL

Operating Voltage	120-277 V
Wattage	20 W

MECHANICAL

Product Dimensions	1 ft x 2 ft
--------------------	-------------

ORDERING

Warranty	1 y
----------	-----

APPLICATIONS

- Office ceiling grid lighting
- Commercial corridor illumination
- Retail interior lighting
- Light industrial workspace lighting
- Educational facility classrooms

slug	value	source	confidence
cct_k	6,000 K	pdf	high
led_lifetime_h	50,000 h	db	high
operating_voltage	120–277 V	db	high
wattage	20 W	db	high
product_dimensions	1 ft x 2 ft	pdf	medium
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY