



2x2 ft LED Panel Light, 30W, 120-277V Input, 50,000-Hour Lifetime

- Draws 30W, sized for 2×2 ft drop ceiling grid openings
- Accepts 120-277V input for broad electrical compatibility
- Rated for 50,000-hour LED lifetime
- Functions as a direct replacement for standard troffer fixtures
- Backed by a 1-year limited warranty

OVERVIEW

The 9-P2×2-30W-H is a 30W LED panel light designed as a direct replacement for standard 2×2 ft drop ceiling troffer fixtures in commercial and industrial applications. It suits office spaces, retail environments, schools, and similar interior settings where recessed grid ceiling lighting is required.

This unit operates on a 120-277V input and carries a rated LED lifetime of 50,000 hours, supporting extended service intervals in continuous-use commercial spaces.

This product carries a 1-year limited warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

ELECTRICAL

Operating Voltage 120-277 V

Wattage 30 W

ORDERING

Warranty 1 y

APPLICATIONS

- Office ceiling grids
- Retail interior lighting
- School classrooms and corridors
- Commercial drop ceiling installations

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120-277 V	db	high
wattage	30 W	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.