



## Panel LED Emergency Driver, 2x2 Backlit Panel, 20-40 W Selectable, 120-277 VAC, 0-10 V Dimming

- 125 lm/W efficacy with isolated, flicker-free driver
- DIP-selectable 20, 25, 30, 35 and 40 W output
- Five-CCT selection: 3000 K, 3500 K, 4000 K, 5000 K, 6000 K
- Lithium-ion emergency battery with 1.5-hour discharge time
- Self-diagnostic 30-second monthly and 90-minute annual tests
- UL listed, tested to UL924, 5-year limited warranty

### OVERVIEW

The LUMIPRO PB Series is a 2'x2' backlit LED flat panel with an integrated emergency driver, sized at 603 × 603 × 37 mm for suspended ceiling grids in offices, schools, healthcare corridors and retail interiors where code-required egress illumination is part of the lighting layout.

Output is field-configurable by DIP switch across 20, 25, 30, 35 and 40 W and five correlated color temperatures from 3000 K to 6000 K, with 125 lm/W efficacy, CRI 80 and a 120-degree distribution. The isolated, flicker-free driver accepts 120-277 VAC and supports 0-10 V dimming. SMD2835 LEDs are rated for 50,000 hours in an aluminum housing with a white finish, IP20, for dry indoor locations. The emergency driver uses a lithium-ion battery with a 1.5-hour discharge, 24-hour recharge and self-diagnostic 30-second monthly and 90-minute annual tests.

UL listed and tested to UL924 requirements, backed by a 5-year limited warranty.

### SPECIFICATIONS

#### OPTICAL

|                   |                                            |
|-------------------|--------------------------------------------|
| Luminous Flux     | 125 lm                                     |
| Efficacy          | 125 lm/W                                   |
| Color Temperature | 3,000K / 3,500K / 4,000K / 5,000K / 6,000K |
| Selectable CCT    | Yes                                        |
| CRI               | 80                                         |
| Beam Angle        | 120°                                       |
| LED Chip Type     | SMD2835                                    |
| LED Lifetime      | 50,000 h                                   |
| Light Color       | White                                      |

#### ELECTRICAL

|                   |           |
|-------------------|-----------|
| Operating Voltage | 120-277 V |
| Wattage           | 40 W      |
| Power Factor      | 0.9       |
| Dimmer Type       | 0 - 10V   |
| Driver            | Isolated  |

## MECHANICAL

|                    |                 |
|--------------------|-----------------|
| Product Dimensions | 603×603×37 mm   |
| Finish             | White           |
| Material           | Aluminum        |
| Mounting           | Wall/Pole Mount |
| Weight             | 1.54 lb         |


## ORDERING

|          |     |
|----------|-----|
| Warranty | 5 y |
|----------|-----|

## ENVIRONMENTAL

|                               |                        |
|-------------------------------|------------------------|
| IP Rating                     | IP20                   |
| Environmental Rating          | Non - Waterproof       |
| Ambient Operating Temperature | -10–45 °C<br>14–113 °F |

## DIMENSIONS & DIAGRAMS



## INSTALLATION

## CERTIFICATIONS & COMPLIANCE



UL Listed



DesignLights Consortium



ENERGY STAR

## APPLICATIONS

Suspended ceiling grids in offices

School classrooms and corridors

Healthcare exam and treatment rooms

Retail sales floors

Code-required egress lighting zones

PROVENANCE — REVIEW COPY ONLY

| slug                 | value                                      | source | confidence |
|----------------------|--------------------------------------------|--------|------------|
| lumens               | 125 lm                                     | pdf    | high       |
| efficacy_lm_per_w    | 125 lm/W                                   | db     | high       |
| cct_k                | 3,000K / 3,500K / 4,000K / 5,000K / 6,000K | both   | high       |
| cct_selectable       | Yes                                        | db     | high       |
| cri                  | 80                                         | db     | high       |
| beam_angle_deg       | 120°                                       | both   | high       |
| led_chip_type        | SMD2835                                    | db     | high       |
| led_lifetime_h       | 50,000 h                                   | pdf    | high       |
| color                | White                                      | db     | high       |
| operating_voltage    | 120–277 V                                  | pdf    | high       |
| wattage              | 40 W                                       | pdf    | high       |
| power_factor         | 0.9                                        | db     | high       |
| dimmer_type          | 0 - 10V                                    | db     | high       |
| driver               | Isolated                                   | db     | high       |
| product_dimensions   | 603×603×37 mm                              | db     | high       |
| finish               | White                                      | db     | high       |
| material             | Aluminum                                   | db     | high       |
| mount_type           | Wall/Pole Mount                            | db     | high       |
| weight               | 1.54 lb                                    | pdf    | high       |
| ip_rating            | IP20                                       | db     | high       |
| environmental_rating | Non - Waterproof                           | db     | high       |
| ambient_temp_c       | -10–45 °C                                  | pdf    | high       |
| warranty_years       | 5 y                                        | db     | high       |

Specifications subject to change without notice.