



2x2 LED Troffer, 36W, 3500/4000/5000K Tunable, 4680 Lumens, ETL Listed

- Delivers 4680 lumens at 36W for 125 lm/W efficacy
- Tunable 3500/4000/5000K color temperature selection
- 0-10V dimmable with CRI of 80 for visual comfort
- Rated IP20 with 150° beam angle and PC diffuser lens
- Operates across 120-277V input and -20 to 45°C ambient range
- ETL and DLC listed, backed by a 3-year warranty

OVERVIEW

The 2×2 LED Troffer is designed for commercial and institutional ceiling grid applications, offering selectable wattage and tunable color temperature to accommodate a range of installation requirements. Its PC diffuser lens promotes even light distribution while reducing glare, making it suitable for offices, retail spaces, and similar interior environments. The fixture operates on 120-277V input, delivers 4680 lumens at 36W with an efficacy of 125 lm/W, and supports 0-10V dimming along with a CRI of 80. This product carries ETL and DLC listings and comes backed by a 3-year manufacturer warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	4,680 lm
Efficacy	125 lm/W
Color Temperature	3,500K / 4,000K / 5,000K
CRI	80
Beam Angle	150°
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Product Dimensions	26 × 5 × 26 in
Finish	White
Weight	12.08 lb

ORDERING

Warranty	3 y
----------	-----

ELECTRICAL

Operating Voltage	120-277 V
Wattage	36 W
Dimmer Type	0 - 10V

ENVIRONMENTAL

IP Rating	IP20
Ambient Operating Temperature	-20-45 °C -4-113 °F

CERTIFICATIONS & COMPLIANCE



ETL Listed



DesignLights Consortium

APPLICATIONS

- Office ceiling grid lighting
- Retail sales floor illumination
- School and institutional interiors
- Healthcare facility corridors
- Commercial hallway and lobby lighting

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	4,680 lm	db	high
efficacy_lm_per_w	125 lm/W	db	high
cct_k	3,500K / 4,000K / 5,000K	db	high
cri	80	db	high
beam_angle_deg	150°	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
operating_voltage	120–277 V	db	high
wattage	36 W	db	high
dimmer_type	0 - 10V	db	high
product_dimensions	26 × 5 × 26 in	db	high
finish	White	db	high
weight	12.08 lb	db	high
ip_rating	IP20	db	high
ambient_temp_c	-20–45 °C	db	high
warranty_years	3 y	db	high

Specifications subject to change without notice.