



Surface Mount Linear LED Light 40W
5000K 3200lm Polycarbonate IP44

- Delivers 3200 lumens at 40W for indoor task and ambient lighting
- 5000K color temperature with CRI of 80 for accurate color rendering
- IP44 rated for protection against dust and water splashes
- Full polycarbonate construction for impact resistance and durability
- Integrated IC driver operating at 120Vac for stable output
- ETL certified with 2-year manufacturer warranty

OVERVIEW

The Lumipro SML Series is a surface mount linear LED fixture designed for indoor commercial and industrial applications. Its polycarbonate construction provides durability in environments where impact resistance is a consideration, and the IP44 rating offers protection against dust ingress and water splashes.

The fixture operates at 120Vac and consumes 40W, delivering 3200 lumens at a 5000K color temperature. A CRI of 80 supports accurate color rendering, and the integrated IC driver is designed to promote output stability and extended service life.

This fixture is ETL certified and carries a 2-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	3,200 lm
Color Temperature	5,000 K
CRI	80
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Finish	White
Material	Fully polycarbonate

ORDERING

Warranty	2 y
----------	-----

ELECTRICAL

Operating Voltage	120 V
Wattage	40 W
Driver	IC

ENVIRONMENTAL

IP Rating	IP44
-----------	------

CERTIFICATIONS & COMPLIANCE



ETL Listed

APPLICATIONS

- Commercial ceiling installations
- Warehouse and industrial facilities
- Retail and office lighting
- Garages and utility rooms
- Residential ceiling fixtures

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	3,200 lm	db	high
cct_k	5,000 K	db	high
cri	80	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
operating_voltage	120 V	db	high
wattage	40 W	db	high
driver	IC	db	high
finish	White	db	high
material	Fully polycarbonate	db	high
ip_rating	IP44	pdf	high
warranty_years	2 y	db	high

Specifications subject to change without notice.

REVIEW COPY