



LED Track Light, 20W 3-CCT Selectable 1600lm, Black, ETL Listed

- Delivers 1,600 lumens at 20W on 120V AC
- Field-selectable CCT: 3000K, 4000K, or 5000K
- 29-degree beam angle for focused accent lighting
- Aluminum housing in black finish, H125 x Dia81mm
- Rated IP20 for indoor use, -30 to 50°C ambient range
- ETL Listed with 3-year warranty and 50,000-hour LED lifetime

OVERVIEW

The LumiPro HE Series LED Track Light is a directional luminaire designed for commercial accent and display lighting applications. Its 29-degree beam angle makes it well suited for retail, gallery, and hospitality environments where controlled light placement is required.

The fixture operates at 20W on 120V AC and delivers 1,600 lumens with an 80 CRI. A three-position CCT selector allows field adjustment between 3000K, 4000K, and 5000K, providing flexibility across different installation requirements. The housing is constructed of aluminum in a black finish, with a compact form factor measuring 125mm in height and 81mm in diameter, and it is rated IP20 for indoor use across a -30 to 50°C ambient range.

This product carries an ETL Listed certification and is backed by a 3-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,600 lm
Color Temperature	3,000K / 4,000K / 5,000K
CRI	80
Beam Angle	29°
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Product Dimensions	H125*Dia81mm
Finish	Black
Material	Aluminum

ORDERING

Warranty	3 y
----------	-----

ELECTRICAL

Operating Voltage	120 V
Wattage	20 W

ENVIRONMENTAL

IP Rating	IP20
Ambient Operating Temperature	-30-50 °C -22-122 °F

CERTIFICATIONS & COMPLIANCE



ETL Listed

APPLICATIONS

- Retail display lighting
- Gallery and museum accent lighting
- Hospitality interior lighting
- Commercial showroom track systems

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,600 lm	db	high
cct_k	3,000K / 4,000K / 5,000K	db	high
cri	80	db	high
beam_angle_deg	29°	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
operating_voltage	120 V	db	high
wattage	20 W	db	high
product_dimensions	H125*Dia81mm	db	high
finish	Black	db	high
material	Aluminum	db	high
ip_rating	IP20	db	high
ambient_temp_c	-30–50 °C	db	high
warranty_years	3 y	db	high

Specifications subject to change without notice.