



LED Track Light, 20W, 3-CCT Selectable 3000K/4000K/5000K, 1600lm, 29° Beam

- Delivers 1,600 lumens at 20W for accent and display lighting
- Field-selectable CCT: 3000K, 4000K, or 5000K
- 29-degree beam angle for focused directional illumination
- Aluminum housing with white finish, H125 x Dia81mm
- CRI of 80 with 50,000-hour rated LED lifetime
- ETL Listed with 3-year manufacturer warranty

OVERVIEW

The LumiPro HE Series LED Track Light (20W) is designed for commercial and retail interior applications requiring directional accent or display lighting. Its 29-degree beam angle makes it well suited for focused illumination of merchandise, artwork, or architectural features on standard track systems.

The fixture operates on 120V AC and delivers 1,600 lumens at 20W, with a CRI of 80 and an L70 rated life of 50,000 hours. CCT is field-selectable among 3000K, 4000K, and 5000K, allowing a single SKU to accommodate warm, neutral, or cool white lighting requirements. The housing is constructed of aluminum with a white finish and carries an IP20 rating, appropriate for dry indoor environments with an ambient operating range of -30 to 50°C.

This product is ETL Listed and backed by a 3-year manufacturer warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,600 lm
Color Temperature	3,000K / 4,000K / 5,000K
CRI	80
Beam Angle	29°
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Product Dimensions	H125*Dia81mm
Finish	White
Material	Aluminum

ORDERING

Warranty	3 y
----------	-----

ELECTRICAL

Operating Voltage	120 V
Wattage	20 W

ENVIRONMENTAL

IP Rating	IP20
Ambient Operating Temperature	-30-50 °C -22-122 °F

CERTIFICATIONS & COMPLIANCE



ETL Listed

APPLICATIONS

- Retail merchandise display lighting
- Gallery and museum accent lighting
- Commercial interior track lighting systems
- Boutique and showroom spotlighting

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,600 lm	db	high
cct_k	3,000K / 4,000K / 5,000K	db	high
cri	80	db	high
beam_angle_deg	29°	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
operating_voltage	120 V	db	high
wattage	20 W	db	high
product_dimensions	H125*Dia81mm	db	high
finish	White	db	high
material	Aluminum	db	high
ip_rating	IP20	db	high
ambient_temp_c	-30-50 °C	db	high
warranty_years	3 y	db	high

Specifications subject to change without notice.