

12-Inch Pendant Ring Trim, 18W 5-CCT Selectable, Wet Location, Black

OVERVIEW

The A-DD-SH-28-B is a 12-inch pendant ring trim from the Pure Ring Collection, designed for suspended ceiling installations in commercial and residential applications. The black finish and clean circular profile make it suitable for lobbies, corridors, and open-plan spaces requiring a defined architectural lighting element.

The fixture operates at 18W across a 100–277V AC input range and delivers 1,890 lumens at 105 lm/W efficiency. CCT is field-selectable among 2700K, 3000K, 3500K, 4000K, and 5000K, with a default of 3000K. CRI is rated at 80, and rated life exceeds 50,000 hours. The unit is rated for wet locations and supports triac dimming at 120V or 0–10V dimming at 277V, with a compatible dimmer list including select Lutron and Leviton models.

The fixture carries ETL and RoHS certifications and is backed by a 5-year warranty.

SPECIFICATIONS

Power	18 W	Input voltage	100-277 V
Luminous flux	1890 lm	Rated life	50000 h
CCT	2700/3000/3500/4000/5000 K	Warranty	5 years
CRI	80	Operating temp	-10 to +45 °C
Beam angle	120 °	Dimensions	12 in diameter x 7 in depth, 4.92 ft / 9.84 ft suspension cable in

DIMENSION

		ENERGY CHART					
VOLTAGE	100-277V AC 60Hz	MODEL NO	SIZE inches	WATTAGE	EFFICIENCY lm/w	DELIVERED LUMENS	CCT
POWER FACTOR	≥0.9	P719-L188-Z277B5T-W1 P28-971	12"	18W	105LM/W±5%	1890LM±5%	2700K
DIMMABLE	triac dimmer (120V), 0-10V dimmer (277V)						3000K
SURGE PROTECTION	1KV						3500K
							4000K
							5000K

CERTIFICATIONS & COMPLIANCE

