

12-Inch Pendant Ring Trim, 18W 5-CCT Selectable, Wet Location Rated

OVERVIEW

The A-DD-SH-29-W is a 12-inch pendant ring trim from the Pure Ring Collection, designed for suspended ceiling applications in commercial and residential environments. The fixture accepts a 5-CCT selectable light source (2700K, 3000K, 3500K, 4000K, 5000K) with a default setting of 3000K, making it adaptable to a range of lighting specifications without stocking multiple SKUs.

The pendant operates at 18W across a wide input voltage range of 100–277V AC, delivering 1,890 lumens at an efficacy of 105 lm/W. CRI is rated at 80, with a rated life exceeding 50,000 hours. The fixture is wet location rated, suitable for covered outdoor or high-moisture interior environments. Dimming is supported via triac dimmer at 120V or 0–10V dimmer at 277V. Operating temperature range is -10°C to +45°C.

The fixture carries ETL and RoHS certifications and is backed by a 5-year manufacturer warranty.

SPECIFICATIONS

Power	18 W	Input voltage	100-277 V
Luminous flux	1890 lm	Rated life	50000 h
CCT	2700/3000/3500/4000/5000 K	Warranty	5 years
CRI	80	Operating temp	-10 to +45 °C
Beam angle	120 °	Dimensions	12 in diameter x 2 in depth; suspension cable 4.92 ft or 9.84 ft

DIMENSION

		ENERGY CHART					
VOLTAGE	100-277V AC 60Hz	MODEL NO	SIZE inches	WATTAGE	EFFICIENCY lm/w	DELIVERED LUMENS	CCT
POWER FACTOR	≥0.9	P719-L188-Z277B5T-W1 P28-971	12"	18W	105LM/W±5%	1890LM±5%	2700K
DIMMABLE	triac dimmer (120V), 0-10V dimmer (277V)						3000K
SURGE PROTECTION	1KV						3500K
							4000K
							5000K

CERTIFICATIONS & COMPLIANCE



RoHS