



4 in. Anti-Glare Round Recessed Downlight, 9-15W Selectable, 5CCT Tunable, 1200 lm, ETL

- Field-selectable 9 W, 12 W or 15 W input power
- 5CCT tunable output: 2700 K, 3000 K, 3500 K, 4000 K, 5000 K
- COB LED with CRI 90 and 36-degree beam angle
- Die cast aluminum alloy body rated to 50,000 hours
- Triac dimming from 5 to 100 percent, power factor above 0.9
- Air-tight, Type IC rated with junction box included

OVERVIEW

The LUMIPRO 4 in. deep anti-glare round downlight is a commercial-series recessed luminaire supplied with an external isolated driver in an integral junction box. The air-tight, Type IC rated assembly installs directly in insulated ceilings without a separate thermal housing, making it suited to retail, office and hospitality ceilings as well as residential remodel work.

Power is field selectable at 9 W, 12 W or 15 W with a 5CCT tunable output of 2700 K, 3000 K, 3500 K, 4000 K or 5000 K, delivering up to 1200 lm at 80 lm/W with CRI 90 and a 36-degree beam from a COB LED. The die cast aluminum alloy body manages thermal load for 50,000 hours to 70 percent lumen maintenance. Triac dimming covers 5-100 percent on 100-130 V AC circuits, with a power factor above 0.9 and an IP44 rating for damp and wet locations.

ETL and cETL listed under UL file 5002722, with a 5-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,200 lm
Efficacy	80 lm/W
Color Temperature	2,700K / 3,000K / 3,500K / 4,000K / 5,000K
Selectable CCT	Yes
CRI	90
Beam Angle	36°
LED Chip Type	COB
LED Lifetime	50,000 h

ELECTRICAL

Operating Voltage	100-277 V
Wattage	9 W
Power Factor	0.9
Dimmer Type	Triac
Driver	Isolated

MECHANICAL		ENVIRONMENTAL	
Product Dimensions	122*77mm	IP Rating	IP44
Finish	White	Environmental Rating	Suitable for Wet/Damp Locations
Material	Die cast Aluminum Alloy	Ambient Operating Temperature	- 20 °C - 4 °F
Mounting	Wall/Pole Mount		
Weight	30.87 lb		
COMPLIANCE		ORDERING	
UL File Number	5002722	Warranty	5 y

CERTIFICATIONS & COMPLIANCE

ETL

ETL Listed

UL

UL Listed
5002722

APPLICATIONS

- Retail sales floors

Commercial office ceilings

Hotel guest rooms and corridors

Insulated residential ceilings
- Damp - location entryways and soffits

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,200 lm	both	high
efficacy_lm_per_w	80 lm/W	db	high
cct_k	2,700K / 3,000K / 3,500K / 4,000K / 5,000K	both	high
cct_selectable	Yes	db	high
cri	90	db	high
beam_angle_deg	36°	both	high
led_chip_type	COB	db	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	100–277 V	pdf	high
wattage	9 W	pdf	high
power_factor	0.9	db	high
dimmer_type	Triac	db	high
driver	Isolated	db	high
product_dimensions	122*77mm	pdf	high
finish	White	db	high
material	Die cast Aluminum Alloy	db	high
mount_type	Wall/Pole Mount	db	high
weight	30.87 lb	pdf	high
ip_rating	IP44	db	high
environmental_rating	Suitable for Wet/Damp Locations	db	high
ambient_temp_c	-20 °C	db	high
ul_file_number	5002722	db	high
warranty_years	5 y	both	high

Specifications subject to change without notice.