

Ceiling Canopy for LED Pendant Light, Black Finish

OVERVIEW

The A-PL-CC-BK is a ceiling canopy assembly designed for use with the LW-PD40W LED pendant light fixture, finished in black. It supports multiple installation configurations including ceiling surface mount, ceiling with wire, ceiling with extension rod, and H-type track adapter with wire, making it adaptable to a range of commercial interior applications such as retail, hospitality, and gallery spaces.

The canopy measures 5.59" x 6.30" and houses a built-in driver with an anti-glare design. The associated pendant system utilizes CREE COB LED chips, delivering up to 100 lm/W efficacy with CRI options of 83 or 95. The UL-listed driver operates at a power factor of 0.98, supports Triac dimming from 100% to 10%, and is compatible with dimmers from Lutron, Leviton, and similar manufacturers. The system starts instantly with no flicker and no audible noise.

No certifications have been confirmed for the canopy component itself. The driver carries UL certification as noted in the product documentation. Installers should reference all applicable local and national electrical codes during mounting.

SPECIFICATIONS

Power	15, 20, 30, 40, 50 W	Beam angle	15, 30, 45 °
Luminous flux	1500, 2000, 3000, 4000, 5000 lm	Input voltage	120, 200-240, 100-277 VAC
CCT	2700, 3000, 4000, 5000 K	Dimensions	5.59" x 6.30"
CRI	83, 95 Ra		

INSTALLATION

- Built-in driver, anti-glare design
- Finished color: Black, White

Part No.	Qty	Power	LED Type	Lumens Max	CCT	CR	Beam Angle	Dimming
LM-PL-CC	1	15W	A120-15W	1500lm	2700K	83	30°/45°/60°	Track Fix
LM-PL-CC	1	20W	A120-20W	2000lm	2700K	83	30°/45°/60°	Track Fix
LM-PL-CC	1	30W	A120-30W	3000lm	2700K	83	30°/45°/60°	Track Fix
LM-PL-CC	1	40W	A120-40W	4000lm	2700K	83	30°/45°/60°	Track Fix
LM-PL-CC	1	50W	A120-50W	5000lm	2700K	83	30°/45°/60°	Track Fix

Applications:

- Restaurants
- Hotels
- Bars
- Offices
- Stores
- Factories
- Warehouses
- Garages
- Studios
- Stages
- Bars

