

Ceiling Canopy for LED Pendant Light – White Finish

OVERVIEW

The A-PL-CC-WH is a white-finish ceiling canopy accessory designed for use with the LW-PD series LED pendant lights. It supports multiple mounting configurations including ceiling surface, ceiling with wire, ceiling with extension rod, and H-type track adapter with wire, making it adaptable to a range of commercial installation requirements such as retail, hospitality, and gallery environments.

The canopy measures 5.59" x 6.30" (142 x 160 mm) and is finished in white. It is compatible with pendant fixtures utilizing CREE COB LED technology, UL-certified drivers, and Triac dimming systems that operate smoothly from 100% down to 10%. Compatible dimmers include Lutron, Leviton, Smart Home, and Arctic Lighting. The built-in driver design supports a power factor of 0.98 with no flicker and instant start operation.

No certifications have been confirmed for the canopy accessory itself. Installer should de-energize the circuit prior to installation and mount only on a 4" octagonal j-box. J-box and mounting hardware are supplied by others.

SPECIFICATIONS

Power	15, 20, 30, 40, 50 W	Beam angle	15, 30, 45 °
Luminous flux	1500, 2000, 3000, 4000, 5000 lm	Input voltage	120, 200-240, 100-277 VAC
CCT	2700, 3000, 4000, 5000 K	IP rating	IP20
CRI	83, 95 Ra		

INSTALLATION

- Built-in driver with glare design
- Frosted/etched back white

Model No.	Size	Power	Voltage	Dimmable	CCT	Beam Angle	Beam Diameter
LA-PL-CC-15	ø2.0x1.0"	15W	AC/DC 120V	Yes	2700K/3000K	15°/30°/45°	1.5"/3.1"
LA-PL-CC-20	ø2.0x1.0"	20W	AC/DC 120V	Yes	2700K/3000K	15°/30°/45°	1.5"/3.1"
LA-PL-CC-30	ø2.0x1.0"	30W	AC/DC 120V	Yes	2700K/3000K	15°/30°/45°	1.5"/3.1"
LA-PL-CC-40	ø2.0x1.0"	40W	AC/DC 120V	Yes	2700K/3000K	15°/30°/45°	1.5"/3.1"
LA-PL-CC-50	ø2.0x1.0"	50W	AC/DC 120V	Yes	2700K/3000K	15°/30°/45°	1.5"/3.1"

Applications:

- Clothing Store/Furniture/Accessory Store
- Supermarket
- Bakery/Restaurant
- Auto Shop
- Museum/Gallery
- Cafe
- Bar

