

## H-Type Track Mount Adapter with 3 ft Wire for LED Pendant Light, White

### OVERVIEW

The A-PL-TM-WH is an H-type track mount adapter with 3 ft wire designed for use with the LW-PD series LED pendant lights, finished in white. It provides a compatible mounting solution for H-type track systems and is suited for retail, hospitality, gallery, and commercial interior applications.

The pendant light series it supports uses CREE COB LED chips with an anti-glare design and built-in driver. The fixtures offer CRI options of 83 or 95, power factor of 0.98, and Triac dimming from 100% to 10%, compatible with Lutron, Leviton, and other common dimmer brands. The driver is UL certified, flicker-free, and instant-start. The 40W model in this size class (5.59" x 6.30") operates on AC100–277V universal voltage.

No additional certifications beyond the UL-certified driver are confirmed in the available source data. Consult product documentation for full compliance details and warranty terms.

### SPECIFICATIONS

<b>Power</b>	15, 20, 30, 40, 50 W	<b>Beam angle</b>	15, 30, 45 °
<b>Luminous flux</b>	1500, 2000, 3000, 4000, 5000 lm	<b>Input voltage</b>	120, 200-240, 100-277 VAC
<b>CCT</b>	2700, 3000, 4000, 5000 K	<b>Dimensions</b>	<math>3.78 \times 5.91 / 5.59 \times 6.30</math>
<b>CRI</b>	83, 95 Ra		

### INSTALLATION

- Built-in driver, anti-glare design.
- Track-mount, black, white.

Part No.	Size	Power	Voltage	Luminous Flux	CCT	Beam Angle	Dimensions
LW-PD-15	1.5" x 1.5"	15W	100-277V	1500lm	2700K	15°	3.78x5.91
LW-PD-20	2.0" x 2.0"	20W	100-277V	2000lm	2700K	15°	3.78x5.91
LW-PD-30	3.0" x 3.0"	30W	100-277V	3000lm	2700K	15°	3.78x5.91
LW-PD-40	4.0" x 4.0"	40W	100-277V	4000lm	2700K	15°	3.78x5.91
LW-PD-50	5.0" x 5.0"	50W	100-277V	5000lm	2700K	15°	3.78x5.91

**Applications:**

- Restaurants/Bars/Lounges/Event spaces
- Hotels/Restaurants
- Retail shops
- Museum/Gallery
- Art
- Bar

