



Retrofit LED Downlight, 15W, 1060lm, 3000K, Dimmable, CRI 90+

- Delivers 1,060 lumens at 15W for 70 lm/W efficacy
- 3000K color temperature with CRI of 90 for accurate color rendering
- Dimmable operation for flexible light-level control
- Aluminum housing with white finish rated -20°C to 40°C ambient
- Rated for 50,000 hour LED lifetime
- ETL listed with Energy Star and FCC certification

OVERVIEW

The Lumipro RS Series Gimbal LED Downlight is a directional recessed fixture designed for commercial and residential retrofit applications where adjustable beam aiming is required.

Rated at 15W with an output of 1060 lumens, this downlight operates on 120V and is dimmable for flexible light-level control. It delivers a CRI of 90, a 3000K color temperature, an efficacy of 70 lm/W, and a rated lifetime of 50,000 hours. The aluminum housing carries a white finish and is rated for ambient operating temperatures from -20°C to 40°C.

This product is ETL listed and carries Energy Star and FCC certification.

SPECIFICATIONS

OPTICAL

Luminous Flux	1,060 lm
Efficacy	70 lm/W
Color Temperature	3,000 K
CRI	90
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Finish	White
Material	Aluminum
Mounting	Recessed

ORDERING

Warranty	7 y
----------	-----

ELECTRICAL

Operating Voltage	120 V
Wattage	15 W
Dimmer Type	Dimmable

ENVIRONMENTAL

Ambient Operating Temperature	-20-40 °C -4-104 °F
-------------------------------	------------------------

CERTIFICATIONS & COMPLIANCE

ETL

ETL Listed

ENERGY STAR

ENERGY STAR

FCC

FCC

APPLICATIONS

- Residential ceiling retrofit
- Commercial office lighting
- Hospitality and retail interiors
- Recessed can replacement
- Hallway and corridor lighting

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	1,060 lm	db	high
efficacy_lm_per_w	70 lm/W	db	high
cct_k	3,000 K	db	high
cri	90	db	high
led_lifetime_h	50,000 h	db	high
color	White	db	high
operating_voltage	120 V	db	high
wattage	15 W	db	high
dimmer_type	Dimmable	pdf	medium
finish	White	db	high
material	Aluminum	db	high
mount_type	Recessed	pdf	medium
ambient_temp_c	-20–40 °C	db	high
warranty_years	7 y	db	high

Specifications subject to change without notice.