

Decorative Flush Mount LED Ring Light, 5-CCT Selectable, Black and Gold Trim

OVERVIEW

The A-SM-18-BG is a decorative flush mount LED ring light from the C26 Pure Ring Collection, designed for commercial and residential interior applications where both performance and aesthetics are required. The black and gold trim snaps onto a slim LED panel via a modular DIY design, and installation is simplified through a twist-and-lock bracket system. The fixture is rated for damp locations, making it suitable for lobbies, corridors, and similar environments.

The 9-inch model operates at 18W across a 100–277V AC input range and delivers 1890 lumens at approximately 105 lm/W. CCT is field-selectable among 2700K, 3000K, 3500K, 4000K, and 5000K, with a factory default of 3000K. CRI is Ra80 with R9 greater than 0, SDCM is 5 or less, and beam angle is 120 degrees. The fixture is compatible with both triac dimmers at 120V and 0–10V dimmers at 277V, with rated life exceeding 50,000 hours. Operating temperature range is -10°C to +45°C.

The fixture carries ETL and RoHS certifications and is rated for a fire rating of V0. A 5-year warranty is included.

SPECIFICATIONS

Power	18 W	Input voltage	100-277 V AC 60Hz
Luminous flux	1890 lm	Dimensions	9 in diameter x 1.67 in height in
CCT	2700/3000/3500/4000/5000 K	Rated life	50000 h
CRI	80	Warranty	5 years
Beam angle	120 °	Operating temp	-10 to +45 °C

DIMENSION

CRI	RA80	7"	27.5"	1.67"
R9	>0	9"	28.5"	1.67"
BEAM ANGLE	120°	12"	29.5"	1.67"
Environment	Damp Location	15"	30.5"	1.67"
FIRE RATING	V0			

RECOMMENDED DIMMERS		LUTRON		LEVITON	
DVCL-183P-WH	DVELV-300P-WH	S-600P-WH	MACL-1834-WH	6674	6615-POW
DVSCCL-183P-ES	PD-6WCL-Combo	SELV-300P-IV	DVWCL-1837H-WH	6633	8HCL453PW
DVCL-183B-WH	CPCL-183B-IV	AVP1-1833-WH		8H-18-31-W	

CERTIFICATIONS & COMPLIANCE

