



4-Inch Surface Mount LED Downlight,  
10W 5000K Triac Dimmable, 650lm

- Delivers 650 lumens from a 10W draw at 120V input
- 5000K color temperature with CRI of 90 or above
- 140° beam angle for broad, even light distribution
- Triac dimmable for compatible lighting control systems
- Aluminum construction with white finish, rated for 50,000-hour lifetime
- Backed by a 5-year manufacturer warranty

OVERVIEW

The Lumipro 4-Inch SM Series is a surface-mounted LED downlight designed for commercial and residential ceiling applications where a low-profile fixture is required.

The fixture draws 10W and delivers 650 lumens with a 5000K color temperature and a CRI of 90 or above. It supports triac dimming, has a 140° beam angle, and is rated for a 50,000-hour service life. The unit is constructed from aluminum, finished in white, and operates on 120V input.

This product carries a 5-year manufacturer warranty and is ETL, Energy Star, FCC and LM80 listed.

SPECIFICATIONS

OPTICAL

|                   |          |
|-------------------|----------|
| Luminous Flux     | 650 lm   |
| Color Temperature | 5,000 K  |
| CRI               | 90       |
| Beam Angle        | 140°     |
| LED Lifetime      | 50,000 h |

MECHANICAL

|                    |                   |
|--------------------|-------------------|
| Product Dimensions | 6.25 × 1.5 × 6 ft |
| Finish             | White             |
| Material           | Aluminum          |
| Weight             | 0.4 lb            |

ELECTRICAL

|                   |       |
|-------------------|-------|
| Operating Voltage | 120 V |
| Wattage           | 10 W  |
| Dimmer Type       | Triac |

ORDERING

|          |     |
|----------|-----|
| Warranty | 5 y |
|----------|-----|

CERTIFICATIONS & COMPLIANCE

ETL

ETL Listed

ENERGY STAR

ENERGY STAR

FCC

FCC

LM80

LM-80 Tested

APPLICATIONS

- Residential ceiling downlighting
- Commercial hallway and office lighting
- Retail display illumination
- Low-profile retrofit installations

PROVENANCE — REVIEW COPY ONLY

| slug               | value             | source | confidence |
|--------------------|-------------------|--------|------------|
| lumens             | 650 lm            | db     | high       |
| cct_k              | 5,000 K           | pdf    | high       |
| cri                | 90                | db     | high       |
| beam_angle_deg     | 140°              | db     | high       |
| led_lifetime_h     | 50,000 h          | db     | high       |
| operating_voltage  | 120 V             | db     | high       |
| wattage            | 10 W              | db     | high       |
| dimmer_type        | Triac             | pdf    | high       |
| product_dimensions | 6.25 × 1.5 × 6 ft | db     | high       |
| finish             | White             | db     | high       |
| material           | Aluminum          | db     | high       |
| weight             | 0.4 lb            | db     | high       |
| warranty_years     | 5 y               | db     | high       |

Specifications subject to change without notice.

REVIEW COPY