

Fencing Spacer for Mid-Trellis Design, Black, 50x50x5mm

OVERVIEW

The B-F1-SPACER-BK is an aluminum fencing spacer designed for use in mid-trellis and full-trellis composite fence panel installations. It maintains consistent panel spacing and alignment during assembly, and is used in conjunction with side cover spaces, WPC panels, and aluminum structural components within the Suprotect composite fencing system.






The spacer is finished in black via powder spraying, consistent with the black aluminum components used throughout the fencing system. It is specified for placement at average positions across panel gaps during trellis-design installations, contributing to a uniform, structurally sound fence assembly.

SPECIFICATIONS

Dimensions	1.88" W x 0.70" H x 1.96" L (48mm x 18mm x 50mm)	Weight	0.12 kg per 6 pcs
-------------------	--	---------------	-------------------

INSTALLATION

PRIVACY DESIGN (L1800MM*H1800MM/ L5.9FT*H5.9FT)

MATERIALS	MODEL	WIDTH	HEIGHT	LENGTH	COVERAGE	MATERIAL	WEIGHT
	S-CF01	(mm) 7.62" 193MM	(mm) 0.54" 14MM	(mm) 69.29" 1759MM	pc/set 10	Suprotect composite deck	kg 44.7 SET
	POST-UP	(mm) 3.14" 80MM	(mm) 3.14" 80MM	(mm) 35.83" 910MM	pc/set 1 2pc/back	Aluminum	kg 4.59 PCS
	POST CAP	(mm) 3.43" 87MM	(mm) 3.43" 87MM	(mm) 1.29" 33MM	pc/set 1	Aluminum	kg 0.18 PACK
	L-FIX BRACKET	(mm) 2.94" 75MM	(mm) 0.94" 24MM	(mm) 3.2" 81MM	pc/set 4	Aluminum	kg 0.18 PACK
	SCREWS FOR L-FIX AND	(mm) 1.64x18MM	(mm) -	(mm) -	pc/set 4	SSL	kg 0.18 PACK

5