

CCT 1-Zone Wireless Remote, 2.4 GHz GFSK, 30 m Range, Magnetic Mount

OVERVIEW

The C-1Z-CCT-GFSK is a single-zone 2.4 GHz RF wireless remote designed for adjusting color temperature and brightness on compatible MiBoxer/Mi-Light 2.4G series controllers and fixtures. Intended for commercial, hospitality, and architectural lighting applications, it provides independent control of CCT and dimming levels via a slider interface, with link/unlink pairing to supported devices.

The remote operates on 2 x AAA batteries (3 V) with a 15 μ A standby draw, transmits at 6 dBm using GFSK modulation over the 2.4 GHz band, and maintains a control distance of up to 30 m. Operating temperature range is -10 °C to 40 °C. A strong magnetic base is included for wall-mount installation without tools.

The unit carries CE, EMC, and RED certifications per ETSI EN 300 400 V2.2.1, ETSI EN 301 489-1 V2.2.3, and ETSI EN 301 489-3 V2.3.2, with LVD compliance per EN 61347-1:2015+A1:2021 and EN 61347-2-11:2001+A1:2019. No warranty term is specified in available documentation.


SPECIFICATIONS

IP rating	IP20	Operating temp	-10 to 40 °C
Input voltage	3 V		

INSTALLATION



Remove the sticker on the holder



Stick the holder on the wall and put remote on the holder