

## RF Touch Wall Remote, 4-Zone 4-Channel, 2.4GHz, Battery-Powered, 5-in-1 Compatible

### OVERVIEW

The C-5IN1-WP-4 is a 2.4GHz capacitive touch panel remote designed for zone-based control of compatible LED lighting systems, LED controllers, and smart panel controllers. Operating across four independent zones, it supports five control configurations—brightness dimming, CCT adjustment, RGB/RGBW color, and RGB+CCT—making it suitable for multi-zone commercial and residential lighting installations. The B series unit mounts via adhesive tape and runs on 2xAAA batteries (3V DC).

The remote transmits at 6dBm across the 2.4GHz band with a rated control distance of 30 meters. Standby current draw is 20uA, supporting extended battery life in low-activity environments. The touch interface provides brightness adjustment from 1–100%, a 60-second delay-off function, and per-zone link/unlink pairing. Operating temperature range is -10°C to 40°C. Unit dimensions are 86x86x16mm.

No certifications are confirmed in the available source documentation. Contractors should verify regional compliance requirements prior to specification. No warranty terms are stated in the provided datasheet. Consult Poli LED & Signs for current warranty and compliance documentation before project submittal.

### SPECIFICATIONS

<b>Power</b>	0.15 W	<b>Weight</b>	0.3 lb
<b>Input voltage</b>	AC 100–240V V	<b>Operating temp</b>	-10 to 40 °C
<b>Dimensions</b>	86 x 86 x 16 mm (B series) / 86 x 86 x 31 mm (T series) mm		